View NSN Online: https://aerobasegroup.com/nsn/6850-01-121-0945

MAGNAFLUX CORPORATION -- ZL-37 ZYGLO PENETRANT -- 6850-01-121-0945

Product ID:ZL-37 ZYGLO PENETRANT

MSDS Date:07/17/1986

FSC:6850

NIIN:01-121-0945

MSDS Number: BGMTJ === Responsible Party ===

Company Name: MAGNAFLUX CORPORATION

Address:7300 W.LAWRENCE AVENUE

City:CHICAGO

State:IL ZIP:60656 Country:US

Info Phone Num:312-867-8000

Emergency Phone Num:312-867-8000

Pr

eparer's Name:BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name: DISTILLATES, (PETROLEUM) HYDROTREATED MIDDLE

CAS:64742-46-7 RTECS #:JN9379645 Fraction by Wt: 10.0%

Ingred Name: KEROSENE

CAS:8008-20-6

RTECS #:OA5500000 Fraction by Wt: 05.0%

ACGIH TL

V:100MG/CUM Ingred Name: NONYLPHENOL POLYETHOXATE CAS:9016-45-9 RTECS #:MD0900000 Fraction by Wt: 3-7% Other REC Limits: NONE RECOMMENDED Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Health Hazards Acute and Chronic: IRRITATES EYES. Effects of Overexposure:INHALATION:CAUSES DIZZINESS,DROWSINESS,NAUSEA; SKIN:LIQUID IRRITATES BY DISSOLVING SKIN OIL; EYES:VAPORS/LIQUID CAUSES IRRITATION. Medical Cond Aggravated by Exposure: NOT KNOWN. First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT, GIVE OXYGEN: SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS, GET MEDICAL ATTN; EYES: IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING WATER, AND GET MEDICAL ATTENTION. Flash Point Method: PMCC lash Point:>200F/>93C

Extinguishing Media: CARBON DIOXIDE, FOAM.

Fire Fighting Procedures: KEEP CONTAINERS COOL WITH WATER SPRAY. Unusual Fire/Explosion Hazard: WHEN INVOLVING IN COMBUSTION, MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

======== Accidental Release Measures ============

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE

AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.
============= Handling and Storage ==============
Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.
Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.
====== Exp osure Controls/Personal Protection ========
Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY. Ventilation:GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT. Protective Gloves:NITRILE RUBBER GLOVES. Eye Protection:FULL GOGGLES.
Other Protective Equipment:EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT.
Work Hygienic Practices:WASH CONTAMINATED CLOTHES BEFORE RE-USE.WASH THOROUGHLY AFTER HANDLING.
upplemental Safety and Health ITEM IS ZL-37 ZYGLO PENETRAN.PER QPL-25135-15,IT IS QUALIFIED FOR TYPE I,METH D,LEVEL 4 OF MIL-I-25135D.THIS ITEM ALSO AVAILABLE IN THE KITS OF TYPE I,METHOD D LEVEL 4 WITH ZR-10A OR ZR-10B EMULSIFIER.
========= Physical/Chemical Properties ===========
HCC:N1 Boiling Pt:B.P. Text: