

ZIEBART INTERNATIONAL CORP. -- XL5-G(RUST PREVENTIVE) -- 8030-01-127-3683

=====  
Product Identification  
=====

Product ID:XL5-G(RUST PREVENTIVE)

MSDS Date:01/01/1987

FSC:8030

NIIN:01-127-3683

MSDS Number: BGNBW

=== Responsible Party ===

Company Name:ZIEBART INTERNATIONAL CORP.

Emergency Phone Num:313-937-0710

CAGE:DO768

=== Contractor Identification ===

Company Name:ZIEBART INTERNATIONAL CORP ZIEBA  
RT PROD

Address:26500 CAPITOL AVENUE

Box:1290

City:REDFORD

State:MI

ZIP:48239

Phone:800-424-9300 CHEMTREC

CAGE:DO768

Company Name:ZIEBART RUSTPROOFING CO

Address:1290 E MAPLE RD

Box:1290

City:TROY

State:MI

ZIP:48099

Country:US

CAGE:55246

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CALCIUM HYDROXIDE

RTECS #:EW2801000

Fraction by Wt: >1%

ACGIH TLV:5MG/CUM

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by W

t: >1%  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)  
CAS:8002-05-9  
RTECS #:SE7449000  
Fraction by Wt: >1%  
OSHA PEL:400 PPM  
ACGIH TLV:400 PPM; 8990

=====  
Hazards Identification  
=====

Effects of Overexposure:SYMPTMS:MILD DEPRESSION TO CONVULSIONS,LOSS OF CONSCIOUSN.SKN CONTCT:BURNING & IRRIT,DEFATTING,DERMA

=====  
First Aid Measures  
=====

First Aid:INHAL:RE  
MOV TO FRES AIR,GIVE OXYGN,CONTCT DR.EYES:FLUSH  
W/WATER, CONTCT DR. SKIN:REMOV CONTAM CLOTHING,WASH W/WATER.  
INGESTION:DO NOT INDUCE VOMITING, CONTACT PHYSICIAN; GIVE WHITE  
MINERAL OIL.

=====  
Fire Fighting Measures  
=====

Flash Point:100F 38C  
Lower Limits:0.8%  
Upper Limits:6.0%  
Extinguishing Media:FOAM, CO\*2,DRY CHEMICAL, WATER.  
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARAT: REMOV  
ALL SOURC OF IGN  
Unusual Fire/Explosion Hazard:PE  
TROLEUM DISTILLATES ARE A FIRE &  
EXPLOSION HAZARD.VAPORS CAN FLOW TO DISTANT IGNIT SOURCES.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION, PROVIDE ADEQUATE  
VENTILATION,ABSORB W/VERNICULITE OR OTHER ABSOBENT.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN WELL VENTILATED AREA AWAY  
FROM SOURCES OF IGNITION.  
Other Precautions:PREVENT SKIN CONTACT &

AVOID BREATHING VAPORS.

===== Exposure Controls/Personal Protection =====

Ventilation:LOC EXHAUST RECOMMEND.MAINTN ADEQ TRANSFR VELOCITY TO  
PRE(SU

Protective Gloves:BUNA-N-RUBBER

Eye Protection:GOGGLES OR FACE SHIELDS

Other Protective Equipment:BUNA-N-RUBBER GLOVES & APRON.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>350F >177

Vapor Pres: