View NSN Online: https://aerobasegroup.com/nsn/8030-01-127-3683

ZIEBART INTERNATIONAL CORPORATION -- XL5-G -- 8030-01-127-3683

Product ID:XL5-G MSDS Date:01/01/1985 FSC:8030 NIIN:01-127-3683 **MSDS Number: BGNBX** === Responsible Party === Company Name: ZIEBART INTERNATIONAL CORPORATION Emergency Phone Num:313-588-4100 CAGE:DO768 === Contractor Identification === Company Name: TEXAS MICROSYSTEMS INC Address:10503 ROCKLEY RD UNIT 1 80 Box:City:HOUSTON State:TX ZIP:77099-3528 Country:US CAGE:55646 Company Name: ZIEBART INTERNATIONAL CORP ZIEBART PROD Address:26500 CAPITOL AVENUE Box:1290 City:REDFORD State:MI ZIP:48239 Phone:800-424-9300 CHEMTREC CAGE:DO768 Ingred Name: ALIPHATIC HYDROCARBON Fraction by Wt: 44.2% ACGIH TLV:500 PPM Ingred Name:WAX OXIDATE Fraction by Wt: 42.4%

Ingred Name:ASPHALT (PETROLEUM) CAS:8052-42-4 RTECS #:CI9900000 Fraction by Wt: 5.0% ACGIH TLV:5 MG/M3; (FUME);9192

Ingred Name:PETROLEUM SULFONATE Fraction by Wt: 4.5%

Ingred Name:PETROLEUM OIL Fraction by Wt: 3.0%

Effects of Overexposure: INGESTION-DO NOT INDUCE VOMITING. CALL PHYSICIAN.

Flash Point:120F,49C TCC Lower Limits:1.0 Upper Limits:6.0 Extinguishing Media:CO2,FOAM,DRY CHEM Fire Fighting Procedures:NONE

Spill Release Procedures: STOP SPILL; RETURN MATERIAL TO CONTAINER.

Handling and Storage Precautions: KEEP AWAY FROM FLAME

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:PAINTER'S MASK Ventilation:MECHANICAL REQ'D Protective Gloves:NORMALLY NO Eye Protection:GOOD PRACTICE Supplemental Safety and Health

====== Phys

ical/Chemical Properties ============

HCC:F4 Boiling Pt:B.P. Text:>300,149C Spec Gravity:0.876 Evaporation Rate & amp; Reference: