View NSN Online: https://aerobasegroup.com/nsn/8030-01-127-3684

ZIEBART INTERNATIONAL CORP. -- XL5-G(RUST PREVENTIVE) -- 8030-01-127-3684

======== Product Identification ============

Product ID:XL5-G(RUST PREVENTIVE)

MSDS Date:01/01/1987

FSC:8030

NIIN:01-127-3684

MSDS Number: BGNBY === Responsible Party ===

Company Name: ZIEBART INTERNATIONAL CORP.

Emergency Phone Num:313-937-0710

CAGE:DO768

=== Contractor Identification ===

Company Name: ZIEBART INTERNATIONAL CORP ZIEBA

RT PROD

Address:26500 CAPITOL AVENUE

Box:1290

City:REDFORD

State:MI ZIP:48239

Phone:800-424-9300 CHEMTREC

CAGE:DO768

Company Name: ZIEBART RUSTPROOFING CO

Address:1290 E MAPLE RD

Box:1290 City:TROY State:MI ZIP:48099 Country:US CAGE:55246

======= Composition/Information on Ingredients ========

Ingred Name: CALCIUM HYDROXIDE

RTECS #:EW2801000 Fraction by Wt: >1% ACGIH TLV:5MG/CUM

Ingred Name: MINERAL OIL

RTECS #:PY8020000 Fraction by Wt: >1%

ACGIH TLV:5MG/CUM(OIL MST

Ingred Name:PET

RTECS #:SE7449000 Fraction by Wt: >1% OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 8990
========== Hazards Identification ===========
Effects of Overexposure:SYMPTMS:MILD DEPRESSION TO CONVULSIONS.LOSS OF CONSCIOUSN.SKN CONTCT:BURNING & IRRIT,DEFATTING,DERMA
======================================
First Aid:INHAL:REMOV TO FRESH AIR,GIVE OXYGN,CONTCT DR. EYES:FLUSH W/WATER. INGESTIO
N:DO NOT INDUCE VOMITING, CONTACT PHYSICIAN; GIVE WHITE MINERAL OIL.
======================================
Flash Point:100F 38C Lower Limits:0.8% Upper Limits:5.0%
Extinguishing Media:FOAM, CO*2,DRY CHEMICAL, WATER. Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPART: REMOV ALL SOURC OF IGN
Unusual Fire/Explosion Hazard:PETROLEUM DISTILLATES ARE A FIRE & EXPLOSION HAZARD. VAPORS CAN FLOW TO DISTANT IGNIT SOURCES.
========= Accident al Release Measures ===========
Spill Release Procedures:REMOVE SOURCES OF IGNITION, PROVIDE ADEQUATE VENTILATION,ABSORB W/VERNICULITE OR OTHER ABSORBENT.
============ Handling and Storage ==============
Handling and Storage Precautions:STORE IN WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. Other Precautions:PREVENT SKIN CONTACT & AVOID BREATHING VAPORS.
====== Exposure Controls/Personal Protection ========
Ventilation:LOC EXHAUST RECOM

ROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT) CAS:8002-05-9

MEND.MAINTN ADEQ TRANSFR VELOCITY TO PRE(SU

Protective Gloves:BUNA-N-RUBBR

Eye Protection: GOGGLES OR FACE SHIELDS

Other Protective Equipment:BUNA-N-RUBBER GLOVES & APRON.

Supplemental Safety and Health

VENTILATION: VENT EXPLOSIVE CONCENTRATIONS. ELIMINATE IGNITION SOURCES

======== Physical/Chemical Properties ==========

HCC:F4
Boiling Pt:B.P. Text:>350F >177
Vapor Pres: