View NSN Online: https://aerobasegroup.com/nsn/3020-01-144-3803

MOBIL OIL CORPORATION -- AVREX S TURBO 260 -- 9150-01-144-3803

Product ID: AVREX S TURBO 260 MSDS Date:03/19/1988 FSC:9150 NIIN:01-144-3803 **MSDS Number: BGNSY** === Responsible Party === Company Name: MOBIL OIL CORPORATION Address:3225 GALLOWS RD City:FAIRFAX State:VA ZIP:22037 Info Phone Num:703-849-3265 (SHIRLEY CASTILLO) Emergency Phone Num:212-883-4411 CAGE:1G11 2 === Contractor Identification === Company Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING Address:3225 GALLOWS ROAD Box:City:FAIRFAX State:VA ZIP:22037 Country:US Phone:800-662-4525/856-224-4644 CAGE:3U728 Company Name: MOBIL OIL CORPORATION Address:3225 GALLOWS RD City:FAIRFAX State:VA ZIP:22037-0001 Phone: (703) 846-1482 CAGE:1G112

Ingred Name:SYNTHETIC OILS Fraction by Wt: 90% OSHA PEL:5MG/M\*3(OIL MIST) ACGIH T LV:5MG/M\*3(OIL MIST)

Ingred Name:ADDITIVES AND OTHER INGREDIENTS Fraction by Wt: 10%

Ingred Name:ANILINE (SARA III) CAS:62-53-3 RTECS #:BW6650000 Fraction by Wt: 0.0001% OSHA PEL:S, 5 PPM ACGIH TLV:S, 2 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:LD50 ORAL RAT=15G/KG Routes of Entry: Inhalation:NO Skin:UNKNOWN Ingestion:NO Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF OVEREXPOSUR

Ε.

Effects of Overexposure:SLIGHT SKIN IRRITATION. Medical Cond Aggravated by Exposure:NONE NOTED

First Aid:EYES:FLUSH WITH WATER. SKIN:WASH WITH SOAP AND WATER. INHALATION:NOT EXPECTED TO BE A PROBLEM. INGESTION:NOT EXPECTED TO BE A PROBLEM WHEN INGESTED. IF UNCOMFORTABLE SEEK MEDICAL ASSISTANCE.

Flash Point Method:PMCC Flash Point:455F(235C) Lower Limits:0.6 Upper Limits:7.0 Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*2O FOG. Fire Fighting Procedures:WEAR SCBA IN ENCLOSED AREAS. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. USE WATER SPRAY TO FLUSH SPILLS. PREVENT RUNOFF FROM ENTERING STREAMS,DRINKING WTR. Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

Spill Release Procedures: ABSORB IN INERT MATERIAL. SHOVEL UP AND PLACE IN APPROPRIATE D

## **ISPOSAL CONTAINER.**

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED Other Precautions:NONE NOTED BY MFR.

Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VENT. Protective Gloves:AS REQUIRED Eye Pro tection:AS REQUIRED Other Protective Equipment:NONE Work Hygienic Practices:WASH AFTER HANDLING. REMOVE CONTAMINATED CLOTHING Supplemental Safety and Health

HCC:V6 Boiling Pt:B.P. Text:600F(316C) Vapor Pres:0.1 Spec Gravity:1 Viscosity:27.8 CS @100F Solubility in Water:NEGLIGIBLE Appearance and Odor:AMBER LIQUID,MILD ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:EXTREME HEAT. Hazardous Decomposition Products:CARBON MONOXIDE/CARBON DIOXIDE.

Waste Disposal Methods:PRODUCT IS SUITABLE FOR BURNING IN ENCLOSED CONTROLLED BURNER OR DISPOSAL BY SUPERVISED INCINERATION. PRODUCT IS SUITABLE FOR REPROCESSING IN APPROVED RECYCLING FACILITY. BURNING MAY BE LIMITED BY RCR A. COMPLY WITH FEDERAL,STATE AND LOCAL REGUL

## ATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.