

GENERAL ELECTRIC CO., SILICONE PRODUCT DIV. -- RTV159 -- 8040-01-154-3111

=====
Product Identification
=====

Product ID:RTV159

MSDS Date:03/05/1990

FSC:8040

NIIN:01-154-3111

MSDS Number: BGP GD

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO., SILICONE PRODUCT DIV.

Address:HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330/266-2641

Emergency Phone

Num:518-237-3330/FAX (73) 518-233-3795

Preparer's Name:DA POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name:EATON CORP PRESSURE SENSORS DIV

Address:15 DURANT AVE

Box:City:BETHEL

State:CT

ZIP:06801-1901

Country:US

Phone:203-796-6000

CAGE:02750

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

=====
Composition/Information on Ingredie

nts =====

Ingred Name:SILANE, METHYLTRACETOXY-
CAS:4253-34-3
RTECS #:VV4500000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:TRADE SECRET (HAZARDOUS)
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TRADE SECRET (NON-HAZARDOUS)
Fraction by Wt: 21.78%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:
YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INGESTION: NONE KNOWN. SKIN
CONTACT: UNCURED PRODUCT CONTACT WILL IRRITATE LIPS, GUMS AND
TONGUE. UNCURED PRODUCT MAY IRRITATE THE SKIN. INHALATION: APPLIES
ONLY IN UNCURED STATE. MAY CUASE MILD RESPIRATORY IRRITATION.
EYES: UNCURED PRODUCT CONTACT IRRITATES EYES. CHRONIC: NONE KNOWN.
Effects of Overexposure:FOR UNCURED PRODUCT-EYE:IRRITATION.SKIN:
IRRITANT. INHALA
TION: MILD RESPIRATORY IRRITATION. INGESTION: NONE
KNOWN.
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:INGESTION: RINSE MOUTH WITH WATER SEVERAL TIMES. INHALATION:
MOVE PERSON TO FRESH AIR. EYES: IN CASE OF CONTACT, IMMEDIATELY
FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET
MEDICAL A TTENTION IF IRRITATION PERSISTS.

===== Fire Fighting Measures =====

=====

Flash Point Method:TOC
Flash Point:>400F/>204C
Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:COLLECT SPILL BY SCRAPING, WIPING, OR
ABSORBING WITH INERT MATERIAL,PLACE IN CLOSABLE CONTAINER. WASH
SPILL ARE WITH DETERGENT SOLUTION. FOLLOW ALL SAFETY PRECAUTIONS
GIVEN.

Neutralizing Agent:NONE

===== Handling and Storage =====

=====

Handling and Storage Precautions:USE ONLY IN WELL VENTILATED AREA.
ACETIC ACID VAPORS ARE RELEASED DURING CURING(TUV=10 PPM),MAY
IRRITATE EYES AND SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:GENERAL MECHANICAL
Protective Gloves:RUBBER OR CLOTH
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYEWASH FOUNTAIN
Work Hygienic Practices:AVOID EYE-SKIN CONTACT.REMOVE CONTACT LENSES
BEFORE USE.RE
MOVE SEALANT FROM HANDS BEFORE HANDLING LENSES
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:1.1
Evaporation Rate & Reference: