

VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.) -- 4405-1GR TYPE H TONER PREMIX --
6850-01-167-5227

===== Product Identification =====

Product ID:4405-1GR TYPE H TONER PREMIX

MSDS Date:01/01/1987

FSC:6850

NIIN:01-167-5227

MSDS Number: BGPNZ

=== Responsible Party ===

Company Name:VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

Address:2710 WALSH AVE.

City:SANTA CLARA

State:CA

ZIP:95051-0905

Co

Country:US

Info Phone Num:408-985-5810 OR 800-828-6571

Emergency Phone Num:F46-422-2177 (XEROX CORP, NY)

CAGE:50804

=== Contractor Identification ===

Company Name:VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

Address:2710 WALSH AVE.

Box:City:SANTA CLARA

State:CA

ZIP:95051-0905

Country:US

Phone:716-422-2177 (XEROX CORP, NY)

CAGE:50804

===== Composition/Information on Ingredients =====

Ingred Name:ISOPARAFFINIC PETROLEUM SOLVENT(ISOPAR G);CAS

#64742-48-9(PER MFR); TLV 300

PPM PER MFR

Fraction by Wt: >95%

ACGIH TLV:300PPM(PER MFR)

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL

CAS:128-37-0

RTECS #:GO7875000

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3; 9192

Ingred Name:ROSIN BINDER; PER MFR,CAS #8050-09-7

Ingred Name:MOLYBDATED CARBON BLACK

Ingred Name:ALUMINUM STEARATE; PER MFR,CAS #637-12-7; SEE SUPPLEMENTAL
DATA FOR OTHER COMPONENTS.

===== Hazards Identification =====

Effects of Overexposure:DIRECT INHALATION OF FUMES MAY CAUSE IRRIT

ATION
TO MUCUS MEMBRANES

=====
First Aid Measures
=====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH
W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST: DO NOT INDUCE
VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

=====
Fire Fighting Measures
=====

Flash Point:105F,40C TCC
Lower Limits:0.8
Upper Limits:7.0
Extinguish
ing Media:FOAM,DRY CHEMICAL,CO*2,WATER FOG
Fire Fighting Procedures:AVOID WATER, IT TENDS TO SPREAD HYDROCARBON
SOLVENT FIRES
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCE. ABSORB FREE LIQUID
WITH SAND,SOIL,ETC. PLACE IN DISPOSAL CONTAINER. FLUSH RESIDUE
W/SOAP & WATER. VENTILATE AREA.

=====
Handling and Storage
=====

Handling and Storage
Precautions:KEEP CONTAINER CLOSED. AVOID HDLG NEAR
HEAT, STG LIGHT, SPARKS, OPEN FLAMES, STRG OXIDANTS.
Other Precautions:AVOID BRTHG VAPORS. AVOID PROLONGED OR REPEATED SKIN
CONTACT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE
Ventilation:NONE
Protective Gloves:NONE
Eye Protection:OPTIONAL
Other Protective Equipment:NEOPRENE OR NITRILE GLOVES FOR
PROLONGED/REPEATED SKIN CONT.
Supplemental Safety and Health
MSDS FM MFR DATED:16JUL

85;NIOSH6:1002503DA,DISPERSING
AGENT;NIOSH7:1002504,NEOCRYL-VINYLTOLUENEBUTYLMETHACRYLATE
RESIN;NIOSH8:1000093DY,DYE; WT % & TLVS UNKNOWN;SP GRVTY
RANGE:0.75-0.81.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:160-177C
Vapor Density:5.0
Spec Gravity:0.78
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK LIQUID,SLIGHT ODOR
Percent Volatiles by Volume:>80%

===== Stability and Reactivity Data =====

S
Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS
Stability Condition to Avoid:HEAT, STRONG LIGHT, SPARKS, OPEN FLAMES,
STRONG OXIDANTS
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF LIQUID AND ABSORBANT AT AN APPROVED
DISPOSAL SITE OR FACILITY I/A/W ALL LOCAL, STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is
formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.