

BEESTON -- BEESTON BL-12;LUBRICATING OIL. -- 9150-01-177-5543

=====
Product Identification
=====

Product ID:BEESTON BL-12;LUBRICATING OIL.

MSDS Date:01/01/1987

FSC:9150

NIIN:01-177-5543

MSDS Number: BGPTS

=== Responsible Party ===

Company Name:BEESTON

Address:540 DEERING AV

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Info Phone Num:207-883-5541

Emergency Phone Num:207-883-5541

CAGE:43

728

=== Contractor Identification ===

Company Name:BEESTON

Address:540 DEERING AV

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Phone:207-883-5541

CAGE:43728

=====
Composition/Information on Ingredients
=====

Ingred Name:SYNTHETIC OIL

Other REC Limits:5MG/CUM AS OIL MIST

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 50.0%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DO

T Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF
EYES,SKIN,NOSE,THROAT,CNS EFFECTS,DIZZINESS,HEADACHE &
NAUSEA,MENTAL CONFUSION. CHRONIC:DERMATITIS;CNS EFFECTS
Effects of Overexposure:IRRITATION TO NOSE,& THROAT,MENTAL
DULLNESS,DIZZINESS,HEADACHE & NAUSEA
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDI
TIONS MAY BE
WORSEN.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.CALL M.D.EYES:WASH
THOROUGHLY,SEEK MEDICAL HELP. SKIN:WASH WITH SOAP & WATER
THOROUGHLY.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:445F/229C
Extinguishing Media:USE SUITABLE MEDIA FOR SURROUNDING FIRE.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fi
re/Explosion Hazard:NONE NOTED;USE ADEQUATE VENTILATION

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;WIPE UP ALL
SPILLS WITH ABSORBENT MATERIALS OR ALLOW TO EVAPORATE WITH PLENTY
OF VENTILATION;DRIED RESIDUE IS SLIPPERY;APPLY SWEEPING COMPOUNDS
OR OTHER MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY & WELL VENTILATED

AREA.KEEP AWAY FROM HEAT,WATER,METALS LIKE AL,MG& ZINC.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS IF ABOVE TLV.

Ventilation:LOCALEXHAUST TO MAINTAIN BELOW TLV/PEL

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:EYE WASH,SAFETY SHOWER,APRON.

Work Hygienic Practices:AVOID CONTACT WITH EYES,SKIN AND CLOTHES.DO NOT BREATHE VAPORS/MIST.DO NOT TAKE IN

TERNALLY,HARMFUL OR FATAL.

Supplemental Safety and Health

MSDS RECEIVED BY DGSC-SLM:08 JAN,1988.

=====
===== Physical/Chemical Properties =====

HCC:T4

Boiling Pt:B.P. Text:190F/88C

Vapor Pres:132

Vapor Density:1.3

Spec Gravity:1.22

Evaporation Rate & Reference:1.39 (NO REF)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GOLDEN YELLOW,SWEET PUNGENT ODOR

Percent Volatiles by Volume:52

=====
===== Stability and Reactivity Data =====

Stability In

dicator/Materials to Avoid:YES

STRONG OXIDIZERS,WATER,ALUMINUM

Stability Condition to Avoid:EXTREME HEAT & MOISTURE

Hazardous Decomposition Products:HCL

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE,AND FEDERAL REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United Sta

tes of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.