

D-A LUBRICANT COMPANY,INC. -- D-A WIRE ROPER SAVER -- 9150-01-179-0228

===== Product Identification =====

Product ID:D-A WIRE ROPER SAVER

MSDS Date:03/15/1989

FSC:9150

NIIN:01-179-0228

MSDS Number: BGPWL

=== Responsible Party ===

Company Name:D-A LUBRICANT COMPANY,INC.

Address:1340 W. 29TH STREET

City:INDIANAPOLIS

State:IN

ZIP:46208

Country:US

Info Phone Num:216-391-8300

Emergency Phone Num:317-9

23-5321

CAGE:30719

=== Contractor Identification ===

Company Name:D-A LUBRICANT CO INC SUB OF PREMIER INDUSTRIAL

Address:1340 W 29TH ST

Box:City:INDIANAPOLIS

State:IN

ZIP:46208-4943

Country:US

Phone:317-923-5321/216-391-8300 OTHER HRS

CAGE:30719

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL

CAS:69029-75-0

Fraction by Wt: 5-10%

OSHA PEL:5MG/CUM,AS OIL MIST

ACGIH TLV:5MG/CUM,AS OIL MIST

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA

III)  
CAS:71-55-6  
RTECS #:KJ2975000  
Fraction by Wt: 15-40%  
OSHA PEL:350 PPM/450 STEL  
ACGIH TLV:350 PPM/450STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:LEAD NAPHTHENE  
CAS:61790-14-5  
RTECS #:QK9150000  
Fraction by Wt: 3-7%  
Other REC Limits:NOT SPECIFIED  
OSHA PEL:50 MG/CUM AS LEAD  
ACGIH TLV:0.15MG/CUM,AS LEAD

Ingred Name:ASPHALT (PETROLEUM)  
CAS:8052-42-4  
RTECS #:CI9900000  
Fraction by Wt: 40-70%  
ACGIH TLV:5 MG/M3; (FUME);9192

===== Haza  
rds Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF  
EYES,SKIN,RESPIRATORY OR G.I. TRACT,NAUSEA,CRAMPS,DIARRHEA AND  
OTHER GASTROINTESTINAL DISORDERS.CHRONIC:CNS EFFECTS,BLOOD,LIVER  
AND KIDNEY EFFECTS OR DAMAGE TO LUNG,KIDNEY,STOMACH AND/OR  
PRODUCTIVE SYSTEM.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF

NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:>370F/188C  
Autoignition Temp:Autoignition Temp Text:>500  
Extinguishing Media:DRY CHEMICAL,CO\*2,FOAM,WATERFOG  
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA,IN CONFINED  
SPACE.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE ON

## HEATING

### ===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION:RECOVER FREE LIQUID;USE SUITABLE INERT ABSORBENT MATERIAL AND COLLECT FOR PROPER DISPOSAL.

### ===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES AND SPARKS.  
Other Precautions:AVOID CONTACT WITH SKIN AND EYES.DO NOT BREATHE VA  
PORS.DO NOT EAT,DRINK OR SMOKE IN WORK AREA.

### ===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORG.VAPORS IF ABOVE TLV.  
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY/CHEM GOGGLES  
Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.  
Supplemental Safety and Health

### ===== Physical/Chemical Properties == =====

HCC:V6  
Boiling Pt:B.P. Text:165F/74C  
Melt/Freeze Pt:M.P/F.P Text:-20F/-4C  
Vapor Pres:100  
Vapor Density:4.5  
Spec Gravity:1.2  
Evaporation Rate & Reference: