View NSN Online: https://aerobasegroup.com/nsn/6850-01-181-7178

Product ID:TURCO AIR-TEC #22 MSDS Date:01/01/1987 FSC:6850 NIIN:01-181-7178 MSDS Number: BGPYJ === Responsible Party === Company Name: TURCO PRODUCTS, INC. Emergency Phone Num:614-387-6200 CAGE:D9808 === Contractor Identification === Company Name: TURCO PRODUCTS, INC. DIVISON OF ELF ATOCHEM NORTH AMERICA Address:2000 MARKET ST Box:City:PHILADELPHIA State:PA ZIP:19103-3222 Country:US Phone:215-419-7890 CAGE:61102 Company Name: TURCO PRODUCTS, INC. Box:6200 City:PHILADELPHIA State:PA ZIP:19103 Country:US Phone:215-419-7890 CAGE:D9808 Ingred Name: AROMATIC PETROLEUM SOLVENT, CAS#68477-31-6 (TAKE TLV AS OIL MIST)5MG/CUM Fraction by Wt: 25.0% Ingred Name:2-BUTOXYETHANOL CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 8.0% **OSHA PE**

L:S, 50 PPM ACGIH TLV:S, 25 PPM; 9293

Ingred Name:NONYLPHENOL POLYETHYLENE GYCOL ETHER ,CAS#26027-38-3 RTECS #:MD0906000 Fraction by Wt: 15.0%

Ingred Name:SODIUM NITRITE (SARA III) CAS:7632-00-0 RTECS #:RA1225000 Fraction by Wt: 0.5% EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:SODIUM DODECYL BENZENE SULFONATE ,CAS#25155-30-0 CAS:25155-30-0 RTECS #:DB6825000 Fraction by Wt: 5.0% EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

====

Effects of Overexposure:EYES:MODERATE TO SEVERE IRRITATION;SKIN:IRRIT,DRYING&DEFATTING;INHAL:IRRIT,DIZZ,HEAD,NAUSEA ,SEE SUPD

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

==

Flash Point:>200F/93C(PMCC)

Extinguishing Media:FOAM,CO*2,DRY CHEMICAL.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:NONE NOTED

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; STOP LEAK, VENTILATE THE AREA. CONTAIN LIQUID, ABSORB REMAINING INTO INERT ABSORBENT AND RECOVER FOR PROPER DISPOSAL.

Handling and Storage Precautions:STORE IN COOL DRY AREA.KEEP AWAY FROM OXIDIZERS,NITRITES,AMINES.KEEP CONTAINER CLOSED WHEN NOT IN USE. Other Precautions:AVOID CONTACT WITH SKIN EYES AND CLOTHES.DO NOT INHALE VAPORS/MIST.WASH THOROUGHLY AFTER EACH USE.DO NOT USE CONTAMINATED CLOTHES.DO NOT EAT,DRINK OR SMOKE IN WORK AREA.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH/MSHA APPROVED SCBA/OR RESPIRATOR FOR ORG.V APORS IF ABOV TL Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN