View NSN Online: https://aerobasegroup.com/nsn/6850-01-181-7178

Product ID:FORMULA 4183 MSDS Date:01/01/1987 FSC:6850 NIIN:01-181-7178 MSDS Number: BGPYM === Responsible Party === Company Name: BRULING & COMPANY, INC. Emergency Phone Num:317-923-3211 CAGE:NO152 === Contractor Identification === Company Name: BRULIN AND CO INC Address:2920 DR ANDREW J BROWN AVE Box:270 С ity:INDIANAPOLIS State:IN ZIP:46205-0270 Country:US Phone:317-923-3211 CAGE:94058 Company Name: BRULING & COMPANY, INC. CAGE:NO152

Ingred Name:AROMATIC PETROLEUM HYDROCARBON(30-50%) Fraction by Wt: 40% ACGIH TLV:100PPM

Ingred Name:ETHANOLAMINE CAS:141-43-5 RTECS #:KJ5775000 Fraction by Wt: 3% OSHA PEL:3 PPM/6 STEL ACGIH TLV:3 PPM/6 STEL; 9192

Ingred Name:2-BUTOXYETHANOL CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 7.5% OSHA

======================================
Effects of Overexposure:DIZZINESS,HEADACHE,NAUSEA UPON EXCESSIVE INHALATION.SKIN & EYE IRRITATION.
======================================
First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE A
NYTHING BY MOUTH TO UNCONSCIOUS PERSON.
======================================
Flash Point:>200F/93C(PMCC) Extinguishing Media:WATER Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:DO NOT USE CUTTING OR WELDING TORCH ON OR NEAR DRUM (EVEN EMPTY).
======================================
Spill Release Procedures:WASH TO SANITARY SEWER OR ABSORB ON SOLID ABSORBENT.
======================================
Handling and Storage Precautions:STORE BETWEEN 40 & 120F.AVOID BREATHING SPRAY MIST.
======================================
Respiratory Protection:CARTRIDGE MASK IF TLV IS EXCEEDED. Ventilation:MECHANICAL GENERAL Protective Gloves:RECOMMENDED. Eye Protection:RECOMMENDED. Supplemental Safety and Health MSDS DATED 6-14-85. SPEC:TYPE II
======================================

HCC:N1 Boiling Pt:B.P. Text:212F/100 C Spec Gravity:0.984 Evaporation Rate & Reference: