

BATTENFELD GREASE & OIL CORPORATION OF NEW YORK -- BATAM S-830-RR --
9150-01-197-7690

=====
===== Product Identification =====

Product ID:BATAM S-830-RR

MSDS Date:01/01/1985

FSC:9150

NIIN:01-197-7690

MSDS Number: BGQJR

=== Responsible Party ===

Company Name:BATTENFELD GREASE & OIL CORPORATION OF NEW YORK

Emergency Phone Num:(716) 695-2100

CAGE:EO110

=== Contractor Identification ===

Company Name:BATTEN

FELD GREASE AND OIL CORP OF NEW YORK INC

Address:1174 ERIE AVE

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120-3036

Country:US

Phone:716-695-2100

CAGE:60226

Company Name:BATTENFELD GREASE AND OIL CORP OF NEW YORK INC

Address:1174 ERIE AVE

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120-3036

Country:US

Phone:716-695-2100

CAGE:EO110

=====
===== Composition/Information on Ingredients =====

Ingred Name:LITHIUM 12 HYDROXYSTEARATE; CAS #7620-77-1 PER MFR &
EPA-TSCA,INITIAL INVENTORY

Fraction by Wt: 10.0%

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 33.0%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:POLYALPHAOLEFIN FLUID; CAS #8037-01-4 PER MFR & EPA-TSCA,INITL INVENTORY.

Fraction by Wt: 50.0%

Ingred Name:PHOSPHATE ESTER; CAS #68025-51-4 PER MFR & EPA-TSCA INITL INVENTORY

Fraction by Wt: 05.0%

Ingred Name:ZINC DIAMYLIDITHIOCARBAMATE; CAS #15337-18-5,PER MFR & EPA-TSCA INITL INVENTORY

Fraction by Wt: 02.0%

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE SKIN/EYE MILD IRRITATION.

=====
First Aid Measures
=====

First Aid:SKIN:WASH/FLUSH WITH SOAP & WATER.REMOVE & LAUNDER CONTAMINATED CLOTHING;EYES:FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MIN.GET MEDICAL ATTN;INGESTION: DO NOT INDUCE VOMITING.GIVE PLENTY OF WATER GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:400F-COC/(D-92)

Autoignition Temp:Autoignition Temp Text:460F

Extinguishing Media:WATER FOG,CO*2, DRY CHEM, FOAM, EARTH OR SAND

Fire Fighting Procedures:PER MFR,WATER MAY CAUSE FROTHING

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIM IGNITION SOURCES.USE PROTECTV EQUIP SUCH AS GLOVES & SAFETY GOGGLES.ABSORB WITH SAND OR INERA MATERIAL.SWEEP OR SCOOP UP

AND PLACE IN SALVAGE TANK.KEEP COVERED PENDING
DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS
AWAY FROM HEAT/OPEN FLAMES.
Other Precautions:NONE KNOWN

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:NORMAL ROOM VENTILATION.
Protective Gloves:PVC/NEOPRENE
Eye Protection:AS REQUIRED
Other Protective Equipment:NON
E NORMALLY REQUIRED
Supplemental Safety and Health
MSDS FM MFR UNDATED.MFR STATED 5/28/85 FORMULATION DEVELOPED IAW REV E
OF MIL-G-10924; MFR PRODUCT CODE #10,791.

=====
Physical/Chemical Properties
=====

HCC:V6
Boiling Pt:B.P. Text:700F
Spec Gravity:0.88
Solubility in Water:NEGLIGIBLE
Appearance and Odor:AMBER SMOOTH GREASE-SLIGHTLY SWEET

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN
Stability Condition to Avoid:OPEN FLAMES
Hazardous Decomposition Products:CARBON MONOXIDE IF INCOMPLETE
COMBUSTION

=====
Disposal Considerations
=====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defe

nse. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.