View NSN Online: https://aerobasegroup.com/nsn/6850-01-198-4444

CAMEL TIRE CARE PRODUCTS DIV OF BRIDGE PRODUCT INC -- BK765-1322 LIQUID BUFFER -- 6850-01-198-4444

============= Product Identification =================

Product ID:BK765-1322 LIQUID BUFFER

MSDS Date:01/01/1987

FSC:6850

NIIN:01-198-4444

MSDS Number: BGQKH === Responsible Party ===

Company Name: CAMEL TIRE CARE PRODUCTS DIV OF BRIDGE PRODUCT INC

Address: 4803 HAROLD ABITZ DR

Box:769

City:MUSKOGEE

State:OK

ZIP:74402-076

9

Country:US

Info Phone Num:918-687-5427 / FAX 918-682-1635

Emergency Phone Num:918-687-5427

CAGE:97789

=== Contractor Identification === Company Name:BALKAMP INC

Address:2601 S HOLT ROAD

Box:City:INDIANAPOLIS

State:IN ZIP:46241 Country:US

Phone:317-244-7241

CAGE:70842

Company Name: BRIDGE PRODUCT INC/CAMEL TIRE CARE PRODUCTS DIV

Address:500S 45TH E

Box:769

City:MUSKOGEE

State:OK

ZIP:74403-5000

Country:US

Phone:918-687-5427

CAGE:97789

====== Composition/Information on Ingredients =====

======

| Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Fraction by Wt: 100%. OSHA PEL:350 PPM/450 STEL ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1 |
|---|
| =========== Hazards Identification ============ |
| Effects of Overexposure:ANAESTH EFFECTS MAY OCCUR IN THE RANGE OF 500-1000PPM. |
| ====================================== |
| First Aid:EYE:FLUSH W/C OPIOUS AMOUNT OF WATER;SKIN:WASH WITH SOAP & WATER;INHALE:REMOVE TO FRESH AIR,GIVE ARTFICIAL RESPIRATION IF NEEDED;KEEP WARM AND QUIET;ING:INDUCE VOMIT.CALL PHYSICIAN IMM. |
| ====================================== |
| Flash Point:NONE Lower Limits:8.0 Upper Limits:10.5 Extinguishing Media:WATER FOG Fire Fighting Procedures:SCBA-NOT CONSIDERED A FLAMM LIQ HAZ UNDER NORMAL INDUSTR USE Unusual Fire/Explosion Hazard:NONE SPECIFIED |
| ========= Accidental Release Measures ============== |
| Spill Release Procedures:USE PROPER PROTECT.EQUIP;SM LEAKS:MOP UP.REMOVE TO OUT OF DOORS;LG SPILLS:EVAC AREA.CONTAIN LIQ TRANSFER TO CLOSED METAL CONT.KEEP OUT OF WTR SUPPLY. |
| ========== Handling and Storage =========== |
| Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT,SHOCK,FRICTION. KEEP CONTAINERS CLOSED. Other Precautions:AVOID BREATHNG VAPORS-PHYSICIAN NOTE:OVERE |
| OHIEL FIECAUHOHS.AVOID DREATHING VAFORS-PHI SICIAN NOTE.UVERE |

XPOSURE MAY
TEMPORARILY INCREASE CARDIAC IRRIT.MAINTAIN ADEQ OXYGENATION UNTIL
RECOVERY.AVOID SYMPATOMIMETIC AMINES.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:BELOW 250PPM,NONE-FOR LEVELS UP TO 2% FOR 1/2HR,USE ORG.CANISTR MASK
Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN