

ALTA CHEMICAL CORP. -- F2,AUTOCOM FILM FIXER(AUTOPOSUCHEM KIT) -- 6750-01-200-8179

=====  
Product Identification  
=====

Product ID:F2,AUTOCOM FILM FIXER(AUTOPOSUCHEM KIT)

MSDS Date:06/03/1981

FSC:6750

NIIN:01-200-8179

MSDS Number: BGQLR

=== Responsible Party ===

Company Name:ALTA CHEMICAL CORP.

Emergency Phone Num:(619) 453-5010

CAGE:8L886

=== Contractor Identification ===

Company Name:ALTA CHEMICA

L CORP.

Address:11526 SORRENTO VALLEY ROAD, SUITE F

Box:City:SAN DIEGO

State:CA

ZIP:92121-1314

Country:US

Phone:619-453-5010

CAGE:8L886

Company Name:ANACOMP INC ANACOMP MULTIPRODUX DIV

Address:5960 FAIRMOUNT AVE

Box:82449

City:SAN DIEGO

State:CA

ZIP:92138-9948

Country:US

Phone:619-291-9960

CAGE:05037

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SODIUM SULFITE(ALKALI METAL SULFITE); CAS #7757-83-7

CAS:7757-83-7

RTECS #:WE2150000

&lt; Wt:2.

Ingred Name:AMMONI

UM THIOSULFATE; CAS #7783-18-8

CAS:7783-18-8

RTECS #:XN6465000

&lt; Wt:10.

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

&lt; Wt:2.

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM ACETATE; CAS #127-09-3

CAS:126-96-5

RTECS #:AJ4375000

&lt; Wt:1.

Ingred Name:WATER; CAS #7732-18-5

CAS:7732-18-5

RTECS #:ZC0110000

=====  
===== First Aid Measures =====

First Aid:SKIN:WASH W.SOAP & H\*2O E

YES:FLUSH W. H\*2O. INGESTED:GIVE 2

GLASSES H\*2O; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHINGBY MOUTH.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*20 SPRAY TO COOL CONTR.

Unusual Fire/Explosion

Hazard:NONE NOTED BY MANUFACTURER.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:USE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT.SMALL SPILL:DILUTE W/LG AMT OF WATER & FLUSH TO SEWARAGE;LARGE SPILL:DIKE LIQUID W ABSORBENT.PUMP LIQUID TO COVERED CONTAINERS FOR DISPOSAL.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL D

AMAGE.AVOID ANY PHYSICAL CONTACT. KEEP  
CONTAINERS TIGHTLY CLOSED

Other Precautions:AVOID CONTACT WITH SKIN & CLOTHING.WASH THOROUGHLY  
AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Supplemental Safety and Health

PART B OF A 4-PART KIT(AU

TOPOSCHEM KIT 2996015-15).KEY1:N1.

===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:=100.C, 212.F

Vapor Pres:18

Vapor Density: