

INLAND PACKAGING,INC. -- X-333 GREASE -- 9150-01-228-3389

=====
Product Identification
=====

Product ID:X-333 GREASE

MSDS Date:01/01/1987

FSC:9150

NIIN:01-228-3389

MSDS Number: BGQYL

=== Responsible Party ===

Company Name:INLAND PACKAGING,INC.

Address:ROUTE 4

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-737-6757

Emergency Phone Num:502-737-6757

CAGE:66172

=== Contra

ctor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLPHENYLPOLYSILOXANE FLUID

CAS:63148-52-7

Ingred Name:LITHIUM STEARATE

CAS:4485-12-5

RTECS #:WI4370000

=====
Hazards Identification
=====

LD50 LC50 Mixture:15000MG/KG

Routes of Entry: Inhalation:UNKNOWN

Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:IRRITATION OF SKIN,EYE & RESPIRATORY TRACT ARE LIKELY. CHRONIC:NO DATA AVAILABLE.

Effects of Overexposure:EYES:IRRITATION. SKIN:IRRITATION. INGESTION:VERY LOW TOXICITY;THIS PRODUCT IS A PASTE,INHALATION IS NOT LIKELY.

Medical Cond Aggravated by Exposure:NOT KNOWN TO MFR.

=====
===== First Aid Measures =====

First Aid:EYES:WASH THOROUGHLY WITH WATER FOR 15 MINUTES.CALL MEDICAL ASSIST

ANCE. SKIN:WASH WITH SOAP & WATER. INHALATION:REMOVE TO FRESH AIR,CALL A PHYSICIAN IF NEEDED. INGESTION:INDUCE VOMITING;SEEK MEDICAL H ELP.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:>212F/100C

Extinguishing Media:WATER FOG,CO*2,DRY CHEMICAL,FOAM

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:COMBUSTIBLE;USE REASONABLE CARE.

=====
===== Accidental Release M
easures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION; SCRAPE UP THE PRODUCT AND COLLECT FOR PROPER DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES.MAINTAIN TEMPERATURE 41-77F.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IF THERE IS AN ADEQUATE VENTILATION.

Ven

tilation:GENERAL/MECHANICAL TO PROVIDE ADEQUATE VENTILATION.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:UNIFORM;EYE WASH FOUNTAIN.
Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES.DO NOT
EAT,DRINK OR SMOKE IN WORK AREA.
Supplemental Safety and Health
MSDS RECEIVED BY DGSC-SLM:4 MARCH 1988.

===== Physical/Chemical Properties =====

HCC:V6
Spec Gravity:1.03
Solubility in Water:NEGLIGIBLE
Appearance and Odor:TAN,ODO
RLESS PASTE
Percent Volatiles by Volume: