

A.B.DICK COMPANY -- 4-4315;OFFSET ROLLER CLEANER & BLANKET WASH -- 6850-01-238-9225

=====  
Product Identification  
=====

Product ID:4-4315;OFFSET ROLLER CLEANER & BLANKET WASH

MSDS Date:06/11/1990

FSC:6850

NIIN:01-238-9225

MSDS Number: BGRDW

=== Responsible Party ===

Company Name:A.B.DICK COMPANY

Address:5700 WEST TOUHY AVENUE

City:CHICAGO

State:IL

ZIP:60648

Country:US

Info Phone Num:312-763-1900

E

mergency Phone Num:312-763-1900

Preparer's Name:KENNETH W.PINTER

CAGE:HO951

=== Contractor Identification ===

Company Name:DICK A B CO

Address:7400 CALDWELL AVE

Box:City:NILES

State:IL

ZIP:60714-4628

Country:US

Phone:847-779-1900

CAGE:17638

Company Name:DICK A B CO

Address:5700 WEST TOUHY AVENUE

Box:City:CHICAGO

State:IL

ZIP:60648

Country:US

Phone:312-647-8800

CAGE:HO951

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HYDROTREATED HEAVY NAPHTHA

CAS:64742-48-9

F

raction by Wt: 100.0%  
Other REC Limits:NONE SPECIFIED

Ingred Name:TRICHLOROFLUOROMETHANE (CFC-11) (SARA III)  
CAS:75-69-4  
RTECS #:PB6125000  
Fraction by Wt: 16-21%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:1000 PPM  
ACGIH TLV:C, 1000 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS  
Ozone Depleting Chemical:1

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health

Hazards Acute and Chronic:INGEST: SLIGHT TO MODERATE NAUSEA,  
VOMITING AND DIARRHEA. EYE: SOME IRRITATION, REDNESS, TEARING,  
BLURRED VISION. SKIN: SOME IRRITATION, DEFATTING OR DERMATITIS MAY  
OCCUR WITH PROLONGED OR REPEATED CONTACT. INHALE: MAY CAUSE  
BREATHING DIFFICULTIES, DIZZINESS OR LIGHTHEADEDNESS.

Explanation of Carcinogenicity:DATA PER MSDS

Effects of Overexposure:POSSIBLE RESPIRATORY IRRITATION, HEADACHE,  
DIZZINESS, NAUSEA, FATIGUE.

Medical Cond Aggravated by Exposure:

PERSONS WITH A HISTORY OF AILMENTS

OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR  
RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.  
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER  
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.  
SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND  
WATER. IF  
IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE  
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE  
MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:9>104F,>40C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED

BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.  
Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL  
SURFACES AND OTHER SOURCES OF IGNITION. AVOID SPREADING BURNING  
LIQUID WITH WATER USED FOR COOLING PURPOSES.

===== Accidental Release Measures =====

Spill Release Procedures:MATERIAL IS VOLATILE AND COMBUSTIBLE AND CARE  
SHOULD BE TAKEN TO PREVENT FIRE. SPILLED MATERIAL MAY BE PUMPED  
INTO ANOTHER CONTAINER OR ABSORBED AND REMOVED FROM AREA. KEEP  
SPARKS, FLAMES AND IGNITION SOURCES OUT OF AREA. DON'T INHALE.  
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP PRODUCT CONTAINERS COOL, DRY AND  
AWAY FROM SOURCES OF IGNITION. USE AND STORE WITH ADEQUATE  
VENTILATION.  
Other Precautions:AVOID INHALATION OF VAPORS. PERSONAL CONTACT SHOULD  
BE AVOIDED. ON CONTACT REMOVE SATURATED CLOTHING/SHOES AND  
FLUSH AFFECTED AREAS WITH WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED  
IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.  
Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL EXHAUST ACCEPTABLE.  
Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER  
Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD  
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK  
CLOTHING AND APRON AS REQUIRED.  
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR  
FOOTWEAR.  
Supplemental Safety and Health  
AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO  
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:316F,158C  
Vapor Pres:2.9  
Vapor Density:4.9  
Spec Gravity:0.79  
Solubility in Water:INSOLUBLE  
Appearance and O

Color: CLEAR LIQUID, KEROSENE ODOR  
Percent Volatiles by Volume: 100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

ACIDS, BASES, OXIDIZING AGENTS AND SELECTED AMINES.

Stability Condition to Avoid: HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE AND  
OTHER UNIDENTIFIED COMPONENTS.

===== Disposal Considerations =====

Waste Disposal Methods: CONS

ULT LOCAL AUTHORITIES. DISPOSAL MUST BE MADE

IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek c  
ompetent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.