View NSN Online: https://aerobasegroup.com/nsn/6850-01-263-7247 MAGNAFLUX CORPORATION -- ZL-56 ZYGLO WATER WASHABLE PENETRANT -- 6850-01-263-7247 Product ID:ZL-56 ZYGLO WATER WASHABLE PENETRANT MSDS Date:11/17/1986 FSC:6850 NIIN:01-263-7247 MSDS Number: BGRNM === Responsible Party === Company Name: MAGNAFLUX CORPORATION Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656-3504 Country:US Info Phone Num:312-867-8000 Emergency Phone Num:312-867-8000 Preparer's Name: BRUCE C.GRAHAM CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676 ======= Composition/Information on Ingredients ========

Ingred Name:PER MAGNAFLUX CORP MSDS DATED 17NOV86, CONTAINS NO

INGREDIENT SUSPECTED OF BEING HAZARDOUS

RTECS #:99999992Z Fraction by Wt: 100.0%

=======

====== Hazards Identification ============

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IRRITATES EYES ON LIQUID/VAPOR CONTACT.

Effects of Overexposure:INHALATION:CAUSES DIZZINESS,DROWSINESS,NAUSEA; SKIN:LIQUID IRRITATES BY DISSOLVING SKIN OIL; EYES:VAPORS/LIQUID CAUSES IRRITATION; INGESTION:MANUFACTURER DIDN'T LIST.

Medical Cond Aggravated by Exposure: NOT KNOWN.

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT, GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS, GET MEDICAL ATTN; EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING WATER, AND GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:>200F/>93C

Extinguishing Media: CARBON DIOXIDE, FOAM.

Fire Fighting Procedure

s:KEEP CONTAINERS COOL WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

======== Accidental Release Measures =============

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVA GE

TANKS.

Neutralizing Agent: NOT KNOWN.

========== Handling and Storage ===============

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection ========

Respira

tory Protection:USE NIOSH APPROVED RESPIRATOR FOR CONFINED AREAS.

Ventilation: GENERAL ROOM VENTILATION TO KEEP BELOW TLV LIMITS.

Protective Gloves: USE NITRILE RUBBER GLOVES IF NEEDED.

Eye Protection: FULL GOGGLES/SAFETY GLASSES W/SIDESHIELD

Other Protective Equipment: NOT KNOWN.

Work Hygienic Practices: WASH OFF PROMPTLY WITH WATER. AVOID SKIN CONTACT.

Supplemental Safety and Health

NSN OF MIL-I-25135, TYPE I, METHOD C, LEVEL4; PER QPL-25135, MAGNAFLUX MAY SUPPLY ONE OF THE FOLLOWING PENETRAN

TS FOR TYPE T,METHOD C,LEVEL 4
UNDER THIS NSN:ZL-56,ZL-38,ZL-37,OR ZL-30B;THIS ENTRY DESCRIBES
ZL-56;PRODUCT NOT AVAILABLE IN AEROSOLCANS.SEE OTHER PNI OF THIS
NSN FOR MORE QUALIFIED ITEMS.

======== Physical/Chemical Properties ===========

HCC:N1

Boiling Pt:B.P. Text:>400F/>204C

Vapor Pres:0.3MM@100F

Vapor Density:>1.0 Spec Gravity:1.01

Evaporation Rate & Evaporation Rate & Reference: NEGLIGIBLE Solubility in Water: NEGLIGIBLE (EMULSIFY)

Appearance and Odor: GREEN OILY LIQUID

===

======= Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid: HEAT, HIGH TEMPERATURES

Hazardous Decomposition Products: EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTH

ORITIES DONOT ALLOW

DUMPING RINSINGS DOWN THE SEWE R, PURIFY RINSINGS WITH MAGNAFLUX TREATMENT SYSTM

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.