View NSN Online: https://aerobasegroup.com/nsn/6850-01-263-8221

MAGNAFLUX CORPORATION -- ZL-27A ZYGLO PENETRANT (PRE 11/1988) -- 6850-01-263-8221

Product ID:ZL-27A ZYGLO PENETRANT (PRE 11/1988)

MSDS Date:06/04/1987

FSC:6850

NIIN:01-263-8221

Kit Part:Y

MSDS Number: BGRPB === Responsible Party ===

Company Name: MAGNAFLUX CORPORATION

Address:7300 W. LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:7

08-867-8000

Emergency Phone Num:708-867-8000

Preparer's Name: BRUCE C. GRAHAM, CH. CHEM

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name: DISTILLATES, (PETROLEUM) HYDROTREATED MIDDLE

CAS:64742-46-7 RTECS #:JN9379645 Fraction by Wt: 10.0%

Ingred Name: KEROSENE

CAS:8

008-20-6 RTECS #:OA5500000 Fraction by Wt: 05.0% ACGIH TLV:100MG/CUM

Ingred Name:DISTILATES(PETROLEUM),CATALYTIC REFORMER FRACTIONATER

RESIDUE, LOW BOILING

CAS:68477-31-6 Fraction by Wt: 25.0%

Ingred Name: UNIDENTIFIED COMPONENTS

Fraction by Wt: 60.0%

========= Hazards Identification ============================

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRITATES EYES,MILDLY. Effects of Overexposure:INHALATION:SPRAY MIST MAY IRRITATE

TO BREATHING

PASSAGES; EYES:LIQUID CONTACT MAY CAUSE IRRITATION; SKIN:SOLVENT IN THE PRODUCT MAY IRRITATE SKIN; INGESTION:NOT NOTED BY MANUFACTURER.

Medical Cond Aggravated by Exposure: NOT STATED BY MANUFACTURER.

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT, GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS, GET MEDICAL ATT N:

EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING WATER, AND GET MEDICAL ATTENTION.

========== Fire Fighting Measures ================

Flash Point Method:PMCC Flash Point:>200F/>93C

Extinguishing Media:CARBON DIOXIDE,FOAM.

Fire Fighting Procedures: KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT SPRAY ON BURNING PRODUCT.

Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION, MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

=========

==== Accidental Release Measures ===========
Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.
======================================
Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVO ID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY. Ventilation:GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT. Protective Gloves:NITRI LE RUBBER GLOVES. Eye Protection:FULL GOGGLES.WHEN SPRAYING OR POURING. Other Protective Equipment:EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT. Work Hygienic Practices:WASH OFF PROMPTLY WITH WATER.AVOID SKIN CONTACT. Supplemental Safety and Health PER QPL-25135-15 OF MIL-I-25135D,THE SET MAY CONSIST OF ZL-22D OR ZL-27A PENETRANT AND ZE-3 OR ZE-4B EMULSIFIER UNDER TYPE I METH B,LVL 3;THIS NSN HAS 2 PARTS IN THE SET; THIS ENTRY REPRESENTS ZL-27A PENETRANT (OLD FORMU LATION); SEE PN INDE FOR NEW ITEM. SEE THE QPL FOR DETAILS FOR EMULSIFIER NAME;KEY1:N1.
========== Physical/Chemical Properties ==========
HCC:N1 Boiling Pt:B.P. Text:410F/210C Vapor Pres:0.5 @100F Vapor Density:>1.0 Spec Gravity:0.95 Solubility in Water:NEGLIGIBLE Appearance and Odor:GREEN LIQUID WITH PETROLEUM DISTILLATE ODOR. Percent Volatiles by Volume:5.0%
========== Stability and Reactivity Data ============

Stability Indicator/Materials to Avoid:YES

MFR STATED "NONE".

Stability Condition to Avoid:HEAT,HIGH TEMPERATURES.

Hazardous Decomposition Products: EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,PUR IFY RINSINGS W/MAGNAFLUX WASTEWAT ER

TREATMNT SYSTM

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.