

MAGNAFLUX CORPORATION -- ZE-3 ZYGLO EMULSIFIER -- 6850-01-263-8221

=====
Product Identification
=====

Product ID:ZE-3 ZYGLO EMULSIFIER

MSDS Date:06/22/1989

FSC:6850

NIIN:01-263-8221

Kit Part:Y

MSDS Number: BGRPC

=== Responsible Party ===

Company Name:MAGNAFLUX CORPORATION

Address:7300 W LAWRENCE AVE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:708-867-8000

Emergency Phone Num:70

8-867-8000

Preparer's Name:BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 50.0%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:"NOT HA

ZARDOUS" INGREDIENTS

Fraction by Wt: 50%

Other REC Limits:NONE ESTABLISHED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:MAY IRRITATE EYES.SEE
OVEREXPOSURE SYMPTOMS.
Effects of Overexposure:INHALATION:NOT LISTED BY
MANUFACTURER.HOWEVER,FINE SPRAY/MIST MAY CAUSE IRRITATION TO
BREATHING PASSAGES; EYES:LIQUID/MIST CAUS
ES IRRITATION;
SKIN:PROLONGED OR REPEATED CONTACT CAUSES IRRITATION BY DI SSOLVING
SKIN OILS; INGESTION:NOT NOTEDBY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY THE MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR; SKIN:REMOVE CONTAMINATED
CLOTHES.WASH OFF PROMPTLY WITH SOAP AND WATER.USE SOOTHING
LOTION.GET MEDICAL HELP IF IRRITATION PERSISTS. EYES:IMMEDIATELY
RINSE EYES WITH
COP IOUS AMOUNT OF WATER.GET MEDICAL ASSISTANCE IF
IRRITATION PERSISTS; INGESTION:NOT STATED BY MANUFACTURER.GET
MEDICAL ATTENTION IF INGESTED.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:325F/163C
Extinguishing Media:CARBON DIOXIDE,FOAM.
Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP
UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG
QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB
LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE
TANKS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL
VENTILATE

D AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATORS FOR CONFINED AREAS.

Ventilation:GENERAL ROOM VENTILATION TO KEEP BELOW TLV LIMITS.

Protective Gloves:USE NITRILE RUBBER GLOVES IF NEEDED.

Eye Prot

ection:FULL GOGGLES/SAFETY GLASSES W/SIDESHIELD

Other Protective Equipment:NOT KNOWN.

Work Hygienic Practices:WASH OFF PROMPTLY WITH WATER.AVOID SKIN CONTACT.

Supplemental Safety and Health

NSN IS FOR A 2 PARTS SET OF MIL-I-25135D I/A/W QPL-25135-15,THE SET UNDER TYPE I,METHOD B,LEVEL 3 MAY CONSIST OF ZL-22D OR ZL-27A PENETRANT AND ZE-3 OR ZE-4B EMULSIFIER.THIS ENTRY DESCRIBES ZE-3;THE Q PL ALSO INDICATES THAT THIS PRODUCT CANGO IN SEVERAL KITS UNDER TYPE I,METH A,B,C,D & LEV

EL 1,2,3,4;KEY1:N1.

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>450F/>232C

Vapor Pres:0.3 @100F

Vapor Density:>1.0

Spec Gravity:0.75

pH:8.0

Solubility in Water:NEGLIGIBLE

Appearance and Odor:VISCOUS PINK LIQUID

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE STATED BY MANUFACTURER.

Stability Condition to Avoid:HEAT,HIGH TEMPERATURES.

Hazardous Decomposition Products:EMITS

OXIDES OF CARBON IF BURNING.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,P URIFY RINSINGS WITH MAGNAFLUX WASTEWATER TREATMENT

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.