

MAGNAFLUX CORPORATION -- SKL-LO SPOTCHECK PENETRANT (LOW ODOR) -- 6850-01-264-8677

=====  
Product Identification  
=====

Product ID:SKL-LO SPOTCHECK PENETRANT (LOW ODOR)

MSDS Date:08/19/1988

FSC:6850

NIIN:01-264-8677

MSDS Number: BGRTY

=== Responsible Party ===

Company Name:MAGNAFLUX CORPORATION

Address:7300 W.LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:312-867-800

0

Emergency Phone Num:312-867-8000

Preparer's Name:BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DISTILATES (PETROLEUM),CATALYTIC REFORMER FRACTIONATER  
RESIDUE,LOW BOILING

CAS:68477-31-6

Fraction by Wt: 10.0%

Ingred Name:PARAFFIN OILS

CA

S:64771-72-8  
Fraction by Wt: 40.0%

Ingred Name:NAPHTHALENE (SARA III)  
CAS:91-20-3  
RTECS #:QJ0525000  
Fraction by Wt: 02.0%  
OSHA PEL:10 PPM/15 STEL  
ACGIH TLV:10 PPM/15 STEL; 9192  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:UNIDENTIFIED COMPONENTS;PER MFR,CONTAINS NO OTHER  
INGREDIENT SUSPECTED OF BEING HAZARDOUS I/A/W INFO IN  
29CFR1910.1200

===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE:IRRITATING TO SKIN &  
EYES;S

IGNIFICANT AMOUNT OF VAPOR INHALATION CAN RESULT IN  
CLUMSINESS & POOR JUDGEMENT,WITH RESULTING DANGER TO THE  
VICTIM.MUCH LIKE ALCOHOL EFFECT.

Effects of Overexposure:INHALATION:CAUSES  
DIZZINESS,NAUSEA,DROWSINESS,FROM INHALATION OF SPRAY MIST;  
SKIN:CAUSES IRRITATION,DISSOLVES SKIN OILS.POSSIBLE DERMATITIS ON  
FREQUENT OR PROLONGED EXPOSURE; EYES:MODERATE IRRITATION BY  
CONTACT OF LIQUID OR SPRAY; INGESTION:LOW TOXICITY,BUT HAZARDOUS IF  
ASPIRATED INTO LUNGS BY INGESTION  
OR VOMITING.

Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF NOT BREATHING,GIVE CPR.IF  
BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:WASH OFF IN FLOWING WATER  
OR SHOWER.RMV CONTAMINATED CLOTHING AND WASH BEFORE RE-USE.USE  
SOOTHING L OTION; EYES:FLUSH EYES WITH A STEADY,GENTLE FLOW OF  
WATER.GET MEDICAL ASST; INGESTION:DO NOT INDUCE VOMITING.IF VOMIT  
IS

INHALED,IT MAY CAUSE ASPHYXIATION.GET MED ATTN IMMEDIATELY;IN  
EMERGENCY CALL MD

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F/>93.3C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE,FOAM

Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC  
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP  
UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG  
QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB  
LIQUID WITH COMMERCIAL ABSORBENT.TRANSFER WASTE MATL IN SALVAGE  
TANKS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL  
VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP  
CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT  
HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.DO  
NOT SPRAY INTO FLAME,ARCS,OR RED HOT SURFACES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN  
CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ventilation:GENERAL VENTILATION TO KEEP CONCENTRATION BELOW LIMITS.

Protective Gloves:NITRILE RUBBER GLOVES

Eye Protection:FULL GOGGLES

Other Protective Equipment:EITHER USE IN A SPRAY BOOTH OR NEXT TO AN  
EXHAUST VENT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.LAUNDER  
CONTAMINATED CLOTHES BEFORE RE-USE.

Supplemental Safety and Health

ITEM IS ONE PART PRODUCT.THIS PENETRANT(SLK-LO) CAN GO WITH EMULSIFIER  
AS ONE PART OF THE KIT;NSN ESTABLISHED IN 1987 IS FOR TYPE  
II,METHOD C;THE QPL-25135-15 SPECIFIED SKL-LO PENETRANT F

OR TYPE

II, METHOD B & C OF MIL-I-25135D; SEE OTHER PNI OF THIS NSN FOR OTHER SIMILAR PRODUCTS FOR TYPE II, METHOD C.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt: B.P. Text: 400F/204C

Vapor Pres: 1.0

Spec Gravity: 0.88

Solubility in Water: NEGLIGIBLE

Appearance and Odor: DARK RED LIQUID, LOW ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition t

o Avoid: HEAT, HIGH TEMPERATURES

Hazardous Decomposition Products: EMITS OXIDES OF CARBON AND NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE), IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, LOCAL REGULATIONS; IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER, PURIFY RINSINGS WITH MAGNAFLUX WASTEWATER SYSTEM.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.