View NSN Online: https://aerobasegroup.com/nsn/6850-01-264-8678

MAGNAFLUX CORPORATION -- SKL-HF/S SPOTCHECK PENETRANT -- 6850-01-264-8678

Product ID:SKL-HF/S SPOTCHECK PENETRANT

MSDS Date: 05/28/1986

FSC:6850

NIIN:01-264-8678

MSDS Number: BGRVB === Responsible Party ===

Company Name: MAGNAFLUX CORPORATION

Address:7300 W. LAWRENCE AVENUE

City:CHICAGO

State:IL ZIP:60656 Country:US

Info Phone Num:312-867-8000

Emergency Phone Num:

312-867-8000

Preparer's Name:BRUCE C. GRAHAM (CHEMIST)

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name:DISTILATES(PETROLEUM),CATALYTIC REFORMER FRACTIONATER RESIDUE,LOW BOILING.

CAS:68477-31-6

Fraction by Wt: >85.0%

Ingred Name: KEROSENE

CAS:8008-20-6

RTEC

S #:OA5500000 Fraction by Wt: 10.0% ACGIH TLV:100MG/CUM

Ingred Name: C.I. SOLVENT YELLOW 14 (SARA III)

CAS:842-07-9

RTECS #:QL4900000 Fraction by Wt: 01.0%

========== Hazards Identification ================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:PRIMARILY CAUSES IRRITATION TO EYES & SKIN.

Effects of Overexposure: INHALATION: CAUSES

DIZZINESS, NAUSEA, DROWSINESS, FROM INHALATION OF SPRAY MIST; SKIN: CAUSES IRRITAT

ION, DISSOLVES SKIN OILS. POSSIBLE DERMATITIS ON

FREQUENT OR PROLONGED EXPOSURE; EYES:MODERATE IRRITATION BY CONTACT OF LIQUID OR SPRAY; INGESTION:LOW TOXICITY,BUT HAZARDOUS IF ASPIRATED INTO LUNGS BY INGESTION OR VOMITING.

Medical Cond Aggravated by Exposure: NOT STATED BY MANUFACTURER.

First Aid:INHALATION:REMOVE TO FRESH AIR.IF NOT BREATHING,GIVE CPR.IF BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:WASH OFF IN FLO WING WATER


OR SHOWER.RMV CONTAMINATED CLOTHING AND WASH BEFORE RE-USE.USE SOOTHING L OTION; EYES:FLUSH EYES WITH A STEADY,GENTLE FLOW OF WATER.GET MEDICAL ASST; INGESTION:DO NOT INDUCE VOMITING.IF VOMIT IS INHALED,IT MAY CAUSE ASPHYXIATION.GET MED ATTN IMMEDIATELY;IN EMERGENCY CALL MD

Flash Point Method:PMCC Flash Point:>200F/93C

Lower Limits:6.0 Upper Limits:1.0

Extinguishing Media: CARBON DIOXIDE, FOAM

Fir



======== Accidental Release Measures ===========

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.

========== Handling and Storage =============

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.DO NOT SPRAY INTO FLAMES,ARCS,HOT SURFACES.

====== Exposure Controls/Person al Protection ========

Respiratory Protection: WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS, WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ventilation: GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT.

Protective Gloves: NITRILE RUBBER GLOVES

Eye Protection: FULL GOGGLES

Other Protective Equipment: EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.LAUNDER CONTAMINATED CLOTHES BEFORE RE-USE.

Supplemental Safety a

nd Health

1 PT PROD; QPL-25135-15 SPECIFIED SKL-HF/S PENETRANT AS TYPE II,METHOD C, PRODUCT OD MIL-I-25135,REV "D";THIS ENTRY DESCRIBES SKL-HF/S PENETRANT;THE QPL-25135-15 ALSO QUALIFIED OTHER PRODUCTS SUCH AS SKL-HT;SKL-LO;SKL-LT;& SKL-WP PENETRANTS OF MAGNAFLUX CORP FOR TY II,METH C;SE OTHER P/N IND FOR THESE ITMS.KEY1:N1.

======== Physical/Chemical Properties ==========

HCC:N1
Boiling Pt:B.P. Text:400F/203C
Vapor Pres:0.5 @100F
Spec Gravity:0.97
Solubili

ty in Water:NEGLIGIBLE Appearance and Odor:DARK RED LIQUID

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT,HIGH TEMPERATURES. Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN.

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the s uitability of this information to their particular situation.