View NSN Online: https://aerobasegroup.com/nsn/6850-01-264-8682

Product ID:ZP-4B ZYGLO DRY DEVELOPER (POST 12/1987) MSDS Date:12/09/1988 FSC:6850 NIIN:01-264-8682 MSDS Number: BGRWD === Responsible Party === **Company Name: MAGNAFLUX CORPORATION** Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656-3504 Country:US Info Phone Num:312-8 67-8000 Emergency Phone Num:312-867-8000 CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS FORMS) (SARA III) CAS:1344-28-1 RTECS #:BD1200000 Fraction by Wt: 05.0% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 M G/M3 TDUST; 9293

Ingred Name:SILICA, AMORPHOUS, DUST CAS:112945-52-5 RTECS #:VV7310000 Fraction by Wt: 05.0% Other REC Limits:6MG/CUM OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3; 8990

Ingred Name:CALCIUM PHOSPHATE (FROM EARLIER MSDS DATED 12/84)-SEE SUPPL DATA. Fraction by Wt: 35.0%

Ingred Name:MAGNESITE CAS:546-93-0 RTECS #:OM2470000 Fraction by Wt: 15.0% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:PENTAERYTHRITOL CAS:115-77-5 RTECS #:RZ2490000 Fraction by Wt: 40.0% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SEE OVEREXPOSURE EFFECTS. Effects of Overexposure:INHALATION: NUISANCE DUST; SKIN: IRRITATING DUE TO DRYING ACTION; EYES: IRRITATING DUE TO GRITTY ACTION/TEXTURE; INGESTION:NOT KNOWN.

First Aid:INHALATION: REMOVE TO FRES

H AIR. GET MEDICAL ASSISTANCE IF
DIFFICULTY IN BREATHING; SKIN: WASH OFF WITH PLENTY OF WATER; EYES: FLUSH WITH COPIOUS AMOUNT OF WATER. IMMEDIATELY GET MEDICAL
ATTENTION IF IRRITATION PERSISTS; INGESTION: NOT STATED BY MFR.
======================================
Flash Point:NONE
Extinguishing Media:WATER, CARBON DIXIDE, FOAM Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.
Unusual Fire/Explosion Hazard:NONE; FLOATING ZP-
4B DUST CAN BE IGNITED BY HIGH ENERGY ARC.
======================================
Spill Release Procedures: USE APPROPRIATE PROTECTIVE EQUIPMENT. AVOID CREATING DUST. SWEEP UP, RETURN TO STOCK UNLESS CONTAMINATED; PLACE IN COVERED CONTAINERS.
======================================
Handling and Storage Precautions:WASH HANDS AFTER USE.STORE IN COOL AND DRY PLACE.KEEP CONTAINER TIGHTLY CLOSED. Other Precautions:AVOID BREATHIN
G DUST.DO NOT GET IN EYES.KEEP DRY.
======================================
Respiratory Protection: USE FILTER MASK, IF USING IN POORLY VENTILATED AREA.
Ventilation:MECHANICAL(GENERAL)
Protective Gloves:NEOPRENE Eye Protection:SAFETY GLASSES
Work Hygienic Practices:WASH HANDS AFTER EACH USE.
Supplemental Safety and Health
ITEM IS ONE PART PRODUCT.QPL-25135-15 COVERS MULTIPLE PRODUCTS UNDER TYPE I, FORM A, OF MIL-I-25135E; NSN (ESTABLISHED IN 1987) IS FOR

Ť

YPE I,FORM A, MATERIAL; THIS NSN REPLACES THE OLD NSN:6850-01-12 1-0950 WHICH WAS FOR GROUPS VIA/VIB UNDER QPL-25135-13,MIL-I-25135C; NO CHANGE IN FORMULATION OCCURED.

HCC:V7 Spec Gravity:0.20 Solubility in Water:NEGLIGIBLE Appearance and Odor:FLUFFY,WHITE POWDER,ODORLESS

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:OXIDES OF CARBON IF HEATED TO BURNING.

Waste Disposal Methods: MANUFACTURER SUGGESTS TREAT AS NON-HAZARDOUS WASTE. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.