View NSN Online: https://aerobasegroup.com/nsn/6850-01-265-2741

MAGNAFLUX CORPORATION -- ZL-2C ZYGLO PENETRANT -- 6850-01-265-2741

Product ID:ZL-2C ZYGLO PENETRANT

MSDS Date:04/04/1986

FSC:6850

NIIN:01-265-2741

MSDS Number: BGRWR === Responsible Party ===

Company Name: MAGNAFLUX CORPORATION

Address:7300 W. LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656-3504 Country:US

Info Phone Num:312-867-8000 Emergency Phone Num:312-867-8

000

Preparer's Name: BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name: DISTILATES (PETROLEUM), CATALYTIC REFORMER FRACTIONATER

RESIDUE, LOW BOILING

CAS:69477-31-6 Fraction by Wt: 10.0%

Ingred Name: KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Fractio

======================================
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IRRITATES EYES. Effects of Overexposure:INHALATION:CAUSES DIZZINESS,DROWSINESS,NAUSEA; SKIN:LIQUID IRRITATES BY DISSOLVING SKIN OIL; EYES:VAPORS/LIQUID CAUSES IRRITATION;INGESTION:NOT LISTED BY MANUFACTURER. Medical Cond Aggravated by Exposure:NOT KNOWN.
======================================
First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN; EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING WATER,AND GET MEDICAL ATTENTION.
======================================
Flash Point Method:PMCC Flash Point:200F/93.3C Lower Limits:6.0% Upper Limits:1.0% Extingui shing Media:CARBON DIOXIDE,FOAM. Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.
========= Accidental Release Measures ==========
Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUI D WITH COMMERCIAL ABSORBE NT.TRANSFER WASTE MATL IN SALVAGE TANKS.
============= Handling and Storage ==============
Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.
====== Exposure Controls/Personal Protect

n by Wt: 15.0% ACGIH TLV:100MG/CUM Respiratory Protection: WEAR RESPIRATOR WITH FILTER CARTRIDGE IF SPRAYING IN UNVENTILATED AREA.

Ventilation: GENERAL VENTILATION OF 1-3 CHANGES PER HOUR, WHEN SPRAYED.

Protective Gloves: NITRILE RUBBER GLOVES.

Eye Protection: FULL GOGGLES.

Other Protective Equipment: NOT KNOWN.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING OR USE.LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

NSN FOR TYPE I,METHOD C LEVEL 2 OF MIL-I-25135D;ZL-2C PENETRANT IS

QUALIFIED PRODUCT FOR TYPE I,METHOD C,LEVELS 1,2,3 & 4 I/A/W QPL-25135-15.THE QPL ALSO SPECIFIED ITEM CAN GO AS PART OF KIT WITH DIFF ERENT EMULSIFIERS;SEE OTHER PNI,SAME NSN,FOR OTHER QUALIFIED PENETRANT OF THE SAME TYPE,METHOD & LEVEL.

HCC:N1

Boiling Pt:B.P. Text:410F/210C

Vapor Pres:0.5 @100F

Vapor Density:>1.0

Spec Gravity:0.91

Solubility in Water: NEGLIGIBLE

Appearance and Odor: GREEN LIQUID, PETROLEUM H

YDROCARBON ODOR.

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

NONE NOTED BY MANUFACTURER.

Stability Condition to Avoid: HEAT, HIGH TEMPERATURES.

Hazardous Decomposition Products: EMITS OXIDES OF CARBON AND NITROGEN.

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE

LOCAL REGULATIONS.IF LOCAL AUTHORITIES PROHIBIT

DUMPING RINSINGS DOWN THE SEWER,P URIFY RINSINGS WITH MAGNAFLUX
WASTEWATER SYSTEM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.