MSDS Date:07/01/1986

FSC:9150

NIIN:01-266-1623

MSDS Number: BGRXT === Responsible Party === Company Name: KILFROST INC

Box:883

City:WOLFBORO

State:NH

ZIP:03894-0883 Country:US

Info Phone Num:603-569-5366

Emergency Phone Num:603-569-5366

CAGE:NO326

=== Contractor Identification ===

Company Name: COLEMAN ROGER ASSOCIATES INC

Address:RT 109A

Box:883

City:WOLFEBORO

State:NH ZIP:03894 Country:US CAGE:52761

Company Name: KILFROST INC

Box:883

City:WOLFBORO

State:NH

ZIP:03894-0883 Country:US

Phone:603-569-5366

CAGE:NO326

======= Composition/Information on Ingredients ========

Ingred Name: ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000 OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM, VAPOR; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:SODIUMSULFONATE

**Ingred Nam** 

CAS:141-43-5 RTECS #:KJ5775000 OSHA PEL:3 PPM/6 STEL ACGIH TLV:3 PPM/6 STEL; 9192 Ingred Name: FATTY ACID SOAPS Ingred Name: HEAVY NAPHTHENIC PETROLEUM OIL DISTILLATE CAS:64741-53-3 RTECS #:PY8034000 Other REC Limits:5NG/CUM,AS OIL MIST ============= Hazards Identification ======================== Health Hazards Acute and Chronic:ACUTE:IRRIATION OF EYES, SKIN AND RESPIRATORY TRACT. Medical Cond Aggravated by Exposure: PRE-EXITING CONDITIONS MAY BE WORSEN. ======== ======== First Aid Measures =============== First Aid:EYES & SKIN:FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINUTES: CALL A PHYSICIAN IF NEEDED. INHALATION: REMOVE TO FRESH AIR INGESTION:DO NOT INDUCE VOMITING:GET MEDICAL ATTENTION. ============ Fire Fighting Measures ========================= Extinguishing Media:WATER SPRAY/FOG,CO\*2,DRY CHEMICAL Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA. Unusual Fire/Explosion Hazard: NONE NOTED ======== Accidental Release Measures ============ Spill Release Procedures: USE PROPER PERSONAL PROTECTION: CONTAIN FREE LIQUID AND RECOVER FOR PROPER DISPOSAL USE INERT ABSORBENT MATERIAL. ============ Handling and Storage =========================== Handling and Storage Precautions: STORE IN COOL DRY AND WELL VENTILATED AREA: KEEP AEAY FROM HEAT AND OXIDIZERS. ====== Exposure Controls/Personal Protection ========

e:ETHANOLAMINE

Respiratory Protection: USE NI

OSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPOR/MIST,IF ABOVE PRL/TLV

Ventilation:LOCAL EXHAUST/GENERAL TO MAINTAIN PEL/TLV

Protective Gloves: NEOPRENE

Eye Protection: CHEMICAL GOGGLES

Other Protective Equipment: APRON, EYE-WASH FOUNTAIN.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN.DO NOT BREATHE

VAPORS/MIST.

Supplemental Safety and Health

======== Physical/Chemical Properties ==========

HCC:V6

Boiling Pt:B.P. Text:WIDE RANGE

Spec Gravity:1.089 Evaporation R

ate & amp; Reference: