View NSN Online: https://aerobasegroup.com/nsn/5970-01-268-2446

Product ID:POLYURETHANE CONCENTRATE (CODE 683030002) MSDS Date:01/27/1988 FSC:5970 NIIN:01-268-2446 MSDS Number: BGSBV === Responsible Party === Company Name:AKZO COATINGS AMERICA INC/SIKKENS AEROSPACE DIV. Address:20846 S NORMANDIE AVE City:TORRANCE

State:CA ZIP:90502 Country:US Info Phone Num:213-320-6800 Emergency Phone Num:213-320-6800 Preparer's Name: ANTONIO A. VELASQUEZ CAGE:EO776 === Contractor Identification === Company Name: AKZO COATINGS AMERICA INC/TROY, MI 48083 CAGE:EO776 Company Name: AKZO COATINGS INC Address:434 W. MEATS STREET Box:City:ORANGE State:CA ZIP:92661 Country:US Phone:714-637-1750; CHEMTREC 800-424-9300 CAGE:98502

Ingred Name:2-ETHOXYETHYL ACETAT E (CELLOSOLVE ACETATE) (EGEEA) CAS:111-15-9 RTECS #:KK8225000 Minumum % Wt:55. Maxumum % Wt:70. OSHA PEL:S,100 PPM ACGIH TLV:S, 5 PPM; 9192

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE (PM ACETATE) CAS:108-65-6 RTECS #:AI8925000 &It; Wt:5.

JURY;SKIN:IRRITATION,DEFATTING,ABSORPTION;INHALATION:COUGHING,HEA DACHE,NAUSEA,VOMIT,UPPER RESPIRATORY TRACT IRRITATION;INGESTION:HEADACHE,NAUSEA,VOMIT,DIZZINESS,WEA KNESS,POSSIBLE KIDNEY,LIVER DAMAGE,GASTRO-INTESTINAL IRRITATION,DIARRHEA.-SEE SUPPLEMENTAL DATA-Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:SEE HEALTH HAZARDS Medical Cond Aggravated by Exposure:NONE EXPECTED

First Aid:EYE

S:FLUSH WITH WATER FOR AT LEAST 15 MINUTES.SEE DOCTOR;SKIN:WASH WITH SOAP & WATER.REMOVE CONTAMINATED CLOTHING;INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED;INGESTION:DRINK 1 OR 2 GLASSE S OF WATER.DO NOT INDUCE VOMIT.SEE DOCTOR IMMEDIATELY.

Flash Point Method:TCC Flash Point:=4.4C, 40.F Lower Limits:1.5 Extinguishing Media:FOAM,CO*2,DRY CHEMICALS Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. U SE WATER TO COOL FIRE EXPOSED CONTAINERS. FIREFIGHTERS WEAR SCBA. Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Spill Release Procedures:WEAR SCBA & PROTECTIVE CLOTHING.REMOVE IGNITION SOURCES.VENTILATE AREA.ABSORB WITH INERT ABSORBENT & PLACE IN APPROPRIATE DISPOSAL CONTAINER.

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,OPEN FLAMES.KEEP CONTAINERS CLOSED. Other Precautions:APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.USE APPROVED BONDING & GROUNDING PROCEDURES.DO NOT TAKE INTERNALLY.AVOID BREATHING VAPORS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR. IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIRLINE RESPIRATOR OR HOOD. Ventilation:LOCAL EXHAUST & MECHANICAL (GENE

RAL) VENTILATION. Protective Gloves: CHEMICAL RESISTANT Eye Protection: CHEMICAL SPLASH GOGGLES Other Protective Equipment: CHEMICAL RESISTANT APRON, BOOTS. EYE BATH & SAFETY SHOWER. Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM. LAUNDER CONTAMINATED CLOTHING. DISCARD CONTAMINATED SHOES & LEATHER. Supplemental Safety and Health HEALTH HAZARDS, CONT'D: CHRONIC:2-ETHOXYETHYL ACETATE CAN CAUSE TESTICULAR CHANGES, BLOOD CHANGES, BIRTH DEFECTS FETOTOXICITY/EMB RYOTOXICITY, KIDNEY & LIVER DAMAGE. NOTICE: INTENTIONALLY CONCENTRATING & IN HALING THE CONTENTS MAY BE HARMFUL OR FATAL.REPEATED & PROLONGED EXPOSURE MAY CAUSE PERMANENT **BRAIN & NERVOUS SYS.DAMAGE**

HCC:F2 Boiling Pt:=145.6C, 294.F B.P. Text:294-313F Vapor Pres:APPROX.3.0 Vapor Density:>1 Spec Gravity:1.06 Evaporation Rate & amp; Reference: