

MAGNAFLUX CORPORATION -- ZL-22D ZYGLO PENETRANT -- 6850-01-268-8788

=====  
Product Identification  
=====

Product ID:ZL-22D ZYGLO PENETRANT  
MSDS Date:11/17/1986  
FSC:6850  
NIIN:01-268-8788  
Kit Part:Y  
MSDS Number: BGSFW  
=== Responsible Party ===  
Company Name:MAGNAFLUX CORPORATION  
Address:7300 W. LAWRENCE AVENUE  
City:CHICAGO  
State:IL  
ZIP:60656-3504  
Country:US  
Info Phone Num:312-867-8000  
Emergency Phone  
Num:312-867-8000  
Preparer's Name:BRUCE C. GRAHAM  
CAGE:37676  
=== Contractor Identification ===  
Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV  
Address:3624 WEST LAKE AVENUE  
Box:City:GLENVIEW  
State:IL  
ZIP:60025  
Country:US  
Phone:847-657-5300/  
CAGE:37676

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DISTILLATES,(PETROLEUM)HYDROTREATED MIDDLE  
CAS:64742-46-7  
RTECS #:JN9379645  
Fraction by Wt: 25.0%

Ingred Name:KEROSENE  
CAS:8008-20-6  
RTECS #:OA5500000  
Fraction by

Wt: 10.0%  
ACGIH TLV:100MG/CUM

Ingred Name:DISTILATES(PETROLEUM),CATALYTIC REFORMER FRACTIONATER  
RESIDUE,LOW BOILING.

CAS:68477-31-6

Fraction by Wt: 20.0%

Ingred Name:UNIDENTIFIED COMPONENTS

Fraction by Wt: 45.0%

=====  
Hazards Identification  
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:IRRITATES EYES,MILDLY.  
Effects of Overexposure:INHALATION:SPRAY MIST MAY IRRITATE TO BREATHING  
PASSAGES; EYES:LIQU  
ID CONTACT MAY CAUSE IRRITATION; SKIN:SOLVENT IN  
THE PRODUCT MAY IRRITATE SKIN; INGESTION:NOT NOTED BY MANUFACTURER.  
Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

=====  
First Aid Measures  
=====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE  
OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING  
WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN;  
EYES:IMM EDIATELY RINSE/FLUSH  
WITH COPIOUS AMOUNT OF RUNNING  
WATER,AND GET MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash Point Method:PMCC  
Flash Point:>200F/>93C  
Extinguishing Media:CARBON DIOXIDE,FOAM.  
Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT  
SPRAY ON BURNING PRODUCT.  
Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC  
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

=====  
Accidental Release Measures  
=====

=====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBENT.T.TRANSFER WASTE MATL IN SALVAGE TANKS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ventilation:GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT.

Protective Gloves:NITRILE RUBBER GLOVES.

Eye Protection:FULL GOGGLES.WHEN SPRAYING OR POURING.

Other Protective Equipment:EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT.

Work Hygienic Practices:WASH OFF PROMPTLY WITH WATER.AVOID SKIN CONTACT.

Supplemental Safety and Health

PER QPL-25135-15 OF MIL-I-25135D,THE SET MAY CONSIST OF ZL-22D OR ZL-27A PENETRANT AND ZE-3 OR ZE-4B EMULSIFIER UNDR TYPE I METHOD B,LEVEL 3;THIS NSN HAS 2 PARTS IN THE SET;THESE EMULSIFIERS & PENETRANTS ARE ALSO QUALIFIED PRODUCTS OF OTHER TYPES,METHODS &

LEVELS.SEE THE QPL;THIS ENTRY OF ZL-22D PENETRANT;KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:410F/210C

Vapor Pres:0.5@100F

Vapor Density:>1.0

Spec Gravity:0.95

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREEN LIQUID WITH PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume:5.0%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MFR STATED "NONE".

Stability Co

Condition to Avoid:HEAT,HIGH TEMPERATURES.

Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,PURIFY RINSINGS W/MAGNAFLUX WASTEWATER TREATMNT SYSTM

Disclaim

er (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.