

MAGNAFLUX CORPORATION -- ZL-17D ZYGLO WATER WASH PENETRANT -- 6850-01-269-4151
===== Product Identification =====

Product ID:ZL-17D ZYGLO WATER WASH PENETRANT

MSDS Date:11/17/1986

FSC:6850

NIIN:01-269-4151

MSDS Number: BGS GF

=== Responsible Party ===

Company Name:MAGNAFLUX CORPORATION

Address:7300 W.LAWRENCE AVE.

City:CHICAGO

State:IL

ZIP:60656

Country:US

Info Phone Num:312-867-8000

Emergency Pho

ne Num:312-867-8000

Preparer's Name:BRUCE C. GRAHAM (CHMIST)

CAGE:37676

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES,(PETROLEUM)HYDROTREATED MIDDLE

CAS:64742-46-7

RTECS #:JN9379645

Fraction by Wt: 40.0%

Ingred Name:KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: 10.0%
ACGIH TLV:100MG/CUM

===== Hazards Identification =====

Health Hazards Acute and Chronic:IRRITATES EYES.
Effects of Overexposure:INHALATION:CAUSES DIZZINESS,DROWSINESS,NAUSEA;
SKIN:LIQUID IRRITATES BY DISSOLVING SKIN OIL; EYES:VAPORS/LIQUID
CAUSES IRRITATION.
Medical Cond Aggravated by Exposure:NOT KNOWN

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS
DIFFICULT,GIVE
OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING
WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN;
EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING
WATER,AND GET MEDICAL ATTENTION; INGESTION: NOT NOTED BY THE
MANUFACTURER.HOWEVER,GET MED ATTN IMMEDIATELY IF INGESTED.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:>200F/>93C
Lower Limits:6.0
Upper Limits:1.0
Ex
tinguishing Media:CARBON DIOXIDE,FOAM
Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT
SPRAY WATER ON BURNING PRODUCT.
Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP
UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG
QTY:WEAR PERSONAL SAFETY E

QUIPMENTS.DIKE AREA FAR AHEAD.ABSORB
LIQUID WITH COMMERCIAL ABSORBENT.T.TRANSFER WASTE MATERIAL TO
SALVAGE TANKS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL
VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP
CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT
HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WEAR A RESPIRATOR WITH ABSORBENT CARTRIDGE IN
POORLY VENTILATED AREAS.IN CONFINED,UNVENTILATED SPACES,WEAR FULL
MASK WITH AIR SUPPLY.

Ventilation:GENERAL VENTILATION TO KEEP BELOW TLV LIMITS.

Protective Gloves:NITRILE RUBBER GLOVES

Eye Protection:CHEMICAL SPLASH/FULL GOGGLES

Work Hygienic Practices:WASH HANDS WITH SOAP/WATER AFTER HANDLING/USE.

Supplemental Safety and Health

ITEM IS ONE PART;NSN

ESTABLISHED IN 1987 WAS FOR TYPE I,METHOD C,LEVEL

2 MATERIALS;THIS ENTRY DESCRIBES ZL-17D PENETRANT WHICH IS TYPE
I,METHOD C,LEVEL 2 ITEM AS SPECIFIED BY QPL-25135-15 FOR MIL-I-25
135,REV "D";SEE OTHER PNI OF THIS NSN FOR OTHER PRODUCTS OF
MAGNAFLUX FOR THE SAME TYPE,METHOD & LEVEL.

=====
Physical/Chemical Properties
=====

HCC:N1

Boiling Pt:B.P. Text:410F/210C

Vapor Pres:0.5 @100F

Vapor Density:>1.0

Spec Gravity:0.88

Solubility in Water:NEGLIGIBLE

Ap

pearance and Odor:GREEN OILY LIQUID,PETROLEUM HYDROCARBON ODOR.

Percent Volatiles by Volume:5.0%

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT,HIGH TEMPERATURES.

Hazardous Decomposition Products:EMITS OXIDES OF CARBON WHEN BURNING

=====
Disposal Considerations
=====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE

D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL REGS PROHIBIT DUMPING
RINSINGS DOWN THE SEWER,PURIFY R INSINGS WITH MAGNAFLUX WATEWATER
TREATMENT SYSTM.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disc

laims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.