

E/M CORP SUB OF GREAT LAKES CHEMICAL CORP -- CP-65 FORTIFIED OIL -- 9150-00-390-5690

=====
Product Identification
=====

Product ID:CP-65 FORTIFIED OIL

MSDS Date:02/26/1993

FSC:9150

NIIN:00-390-5690

MSDS Number: BGSTK

=== Responsible Party ===

Company Name:E/M CORP SUB OF GREAT LAKES CHEMICAL CORP

Address:2801 KENT STREET, U.S.HWY 52

Box:2400

City:WEST LAFAYETTE

State:IN

ZIP:47906

Country:US

Info

Phone Num:317-463-2511

Emergency Phone Num:317-463-2511

Preparer's Name:CHEMICAL COMMUNICATIONS

CAGE:8F024

=== Contractor Identification ===

Company Name:E / M CO. DIV OF MORGAN CHEMICAL PRODUCTS INC

Address:100 COOPER CIR

Box:3969

City:PEACHTREE CITY

State:GA

ZIP:30269

Country:US

Phone:770-261-4835 / FAX: 770-631-0833

CAGE:8F024

=====
Composition/Information on Ingredients
=====

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

OSHA PEL:10 MG/M3 TDUST (MO)

ACG

IH TLV:10 MG/M3 (MO); 8990

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Other REC Limits:5MG/CUM,AS(OILMIST)

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NOT DETERMINED FOR PRODUCT.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MOLYBDENUM COMPOUNDS MAY BE SLIGHTLY

IRRITANT. MINERAL OILS (SOLVENT REFINED) MAY CAUSE SKIN IRRITATION. CAN CAUSE EYE IRRITATION, REDNESS, BLURRED VISION. PROLONGED CONTACT CAN CAUSE SKIN IRRITATION , DERMATITIS. INHALATION CAN CAUSE IRRITATION, CENTRAL NERVOUS SYSTEM DISTURBANCES. INGESTION CAN CAUSE GI TRACT UPSET.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS

CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:EYE IRRITATION, REDNESS, BLURRED VISION; SKIN

IRRITATION, DERMATITIS; RESPIRATORY TRACT IRRITATION, DIZZINESS, NAUSEA, FATIGUE, HEADACHE, UNCONSCIOUSNESS, ASPHYXIATION; GASTROINTESTINAL IRRITATION, NA USEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH COPIOUS AMOUNTS OF WATER, GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS IMPA

URED, GET MEDICAL ATTENTION.

INGESTION: DO NOT IN DUCE VOMITING. KEEP WARM, GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:>300F,>149C

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, HALON

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND FULL FACE-PIECE SELF-CONTAINED BREATHING APPARATUS. DO NOT EXTINGUISH WITH WATER.

Unusual Fire/Explosion Hazard:N

ONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN SPILL WITH ABSORBENT MATERIAL. ELIMINATE IGNITION SOURCES. WEAR GLOVES, GOGGLES AND GAS MASK IF TLV'S ARE EXCEEDED.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:PROTECT FROM PHYSICAL DAMAGE. STORE IN A COOL, DRY, VENTILATED AREA AWAY FROM ACIDS, ALKALIS AND OPEN FLAMES.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN LEVELS BELOW TLV'S. MECHANICAL - USE NON SPARKING EQUIPMENT.

Protective Gloves

:CHEMICAL RESISTANT GLOVES

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spe

c Gravity:< 1

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:NIL

Appearance and Odor:GRAY/BLACK LIQUID, PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:OPEN FLAMES

Hazardous Decomposition Products:IRRITATING AND/OR TOXIC FUMES
INCLUDING SULFUR AND CARBON COMPOUNDS MAY BE RELEASED.

===== Disposal Considerations =====

=====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and discla

ims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.