View NSN Online: https://aerobasegroup.com/nsn/6850-01-264-8677

Product ID: VP-30 PENETRANT MSDS Date:10/24/1986 FSC:6850 NIIN:01-264-8677 **MSDS Number: BGTBB** === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID STREET **City:SANTA MONICA** State:CA ZIP:90404-3770 Country:US Info Phone Num:213-450-1111 Emergency Phone Num:213-450-1111 CAGE:98733 === Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733 Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC CAS:64742-88-7 **OSHA PEL:500PPM** ACGIH TLV:100PPM Ingred Name:SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC CAS:64742-95-6 **OSHA PEL:500PPM** ACGIH TLV:100PPM

====== Hazard

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MAY CAUSE SLIGHT SKIN IRRITATION;VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT,AND CAUSES CNS DEPRESSION. Effects of Overexposure:EYES/SKIN:LIQUID IS MINIMALLY IRRITATING TO THE EYES AND SLIGHTLY IRRITATING TO THE SKIN.VAPORS CAUSE EYES IRRITATION; INHALATION:VAPORS CAUSE I RRITATION TO NOSE,THROAT AND RESPIRATORY TRACT,AND CAUSE CNS DEPRESSION;INGESTION:MAY CAUSE NAUSEA,GIDDINESS OR HEADACHE,AND POSSIBLE VOMITING. Medical Cond Aggravated by Exposure:PREEXISTING EYE,SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EYES/SKIN:FLUSH WITH PLENTY OF RUNNING WATER.REMOVE VONTAMINATED CLOTHS,AND WASH SKIN WITH SOAP & WATER GET MEDICAL ASST

IF IRRITATION PERSISTS; INHALATION: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHI NG IS DIFFICULT.GIVE ARTIFIICIAL RESPIRATION IF REQUIRED.GET MED HELP IF NEEDED; INGESTION: DO NOT INDUCE VOMITNG.NOTHING BY MOUTH IF VICTIM IS UNCONSCIOUS; GET MEDICAL ASSISTANCE IMMEDIATELY.

Flash Point Method:TCC Flash Point:140F/60C Lower Limits:1.0 Upper Limits:6.0 Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOA M;DO NOT USE DIRECT STREAM OF WATER. Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL

Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRE SHOULD BE COOLED WITH WATER SPRAY TO PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RUPTURE CONTAINER.

Spill Release Procedures: ELIM IGNITI

**ON SOURCES.WEAR APPROPRIATE** PROTECTIVE CLOTHING & RESPIRATOR.DIKE & TRANSFER LIQ TO A SALVAGE TANK.SOAK UP RESIDUE WITH ABSORBENT CLAY, SAND OR OTHR MATL.PLACE RGAS & ABSORBED WASTE MATERL I N COVERED NON-LEAKING CONTAINERS. Handling and Storage Precautions: KEEP AWAY FROM HEAT/IGNITION SOURCES. STROR IN DRY.COOL& VENTILATED LOCATION.DO NOT STORE NEAR OXIDIZING MATERIAL. AVOID PHYSICAL DAMAGE TO CANS. Other P recautions: MINIMIZE SKIN CONTACT. KEEP CONTAINERS CLOSED WHEN NOT IN USE.USE WITH ADEQUATE VENTILATION: AVOID PROLONGED BREATHING OF VAPORS. Respiratory Protection: IF EXPOSURE EXCEEDS TLV, USE NIOSH APPRVD RESPIRATOR TO PREVENT OVEREXPOSURE. Ventilation: PER MANUFACTURER, PROVIDE LOCAL EXHAUST, OR MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV. Protective Gloves: CHEMICAL RESISTANT **Eve Protection: GOGGLES** Other Prote ctive Equipment: EYE WASH FOUNTAINS AND SAFETY SHOWERS. Work Hygienic Practices: WASH WITH SOAP AND WARER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES, MINIMIZE SKIN CONTACT. Supplemental Safety and Health NSN FOR TYPE II, METHOD C OF MIL-I-25135, REVISION "D"; PER QPL-25135-15, THE QUALIFIED PRODUCTS OF MET-L-CHEK ARE VP-30 AND VP-31A PENETRANTS FOR TYPE II, METHOD C. THIS ENTRY DESCRIBES: VP-30 PENETRANT; M FR MAY SUPPLY EITHER VP-30 OR VP-31A UNDER THIS NSN. ============

HCC:F4 Boiling Pt:B.P. Text:368-415F Spec Gravity:0.8 Evaporation Rate & amp; Reference: