

MET-L-CHEK COMPANY -- E-58A EMULSIFIER -- 6850-01-268-6715

=====
Product Identification
=====

Product ID:E-58A EMULSIFIER

MSDS Date:10/31/1986

FSC:6850

NIIN:01-268-6715

MSDS Number: BGTCY

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404-3770

Country:US

Info Phone Num:213-450-1111

Emergency Phone Num:213-450-1111

CAGE:98733

=

== Contractor Identification ==

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 50.0%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE SLIGHT SKIN IRRITATION;
VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY
TRACT.

Effects of Overexposure:EYES:MAY CAUSE IRRITATION; SKIN:SLIGHT
IRRITATION ON CONTACT WITH LIQUID; INHALATION:VAPORS OR MIST OF
PRODUCT MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT. CAN
CAUSE CENTRAL NERVOUS SYSTE
M DE PRESSION. INGESTION:MAY RESULT IN
VOMITING.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES.GET MEDICAL
HELP IR IRRITATION OCCURS OR PERSISTS; SKIN:FLUSH WITH WATER.WASH
WITH LUKE WARM WATER & SOAP.GET MEDICAL HELP FOR PERSISTING
IRRITATION; INHA LATION:REMOVE TO FRESH
AIR.PROVIDE OXYGEN IF
BREATHING IS DIFFICULT.GET MEDICAL ASSISTANCE IF NEEDED;
INGESTION:IF SWALLOWED, INDUCE VOMITING.GET MEDICAL ASSISTANCE.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:232F/111.1C
Upper Limits:3.2
Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOAM; DO
NOT USE DIRECT STREAM OF WATER ON THE FIRE.
Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL
BUNKER GEAR INCLUDIN
G A POSITIVE PRESSURE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST AND/OR RUPTURE IN
INTENSE HEAT OF FIRE. PER MANUFACTURER,PRODUCT MAY IGNITE IN AIR
WHEN EXPOSED TO FLAME AT 775F.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES.WEAR APPROPRIATE
PROTECTIVE CLOTHING AND RESPIRATORS.SOAK UP WITH ABSORBENT.PLACE
WASTE IN SEALED CONTAINERS.FLUSH WITH

WATER.LG LIQ:DIKE LIQUID &
PUMP INTO SALVAGE TANK.ABS ORB RESIDUE WITH COMM ABSORBENT & PUT IN
CLOSED DR

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF
HEAT/IGNITION.STORE IN COOL, DRY & VENTILATED AREA.DO NOT STORE NEAR
OXIDIZING MATERIAL;AVOID PHYSICAL DAMAGE TO CONTAINERS.
Other Precautions:MINIMIZE SKIN CONTACT.AVOID BREATHING VAPORS.

=====
===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:NOT NEEDED IN NORMAL CONDITIONS OR USES WHEN
VAPORS/MIST CONCENTRATIONS ARE BELOW TLV/PEL LIMITS. WEAR NIOSH
APPROVED ORGANIC TYPE RESPIRATOR IN ABSENCE OF PROPER ENVIRONMENTAL
CONTROL.

Ventilation:LOCAL EXHAUST OR MECHANICAL(GENERAL) TO MAINTAIN TLV OR
BELOW TLV LIMITS.

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SAFETY GLASSES OR SPLASH-PROOF GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON TO PREVENT
CLOTHING/SKIN CONTACT.

Work Hygienic Practices:WASH HANDS WITH SOAP & WATER BEFORE EATING,
SMOKING OR USING TOILET FACILITIES;DO NOT EAT/DRINK IN VAPOR
CONTMNTD AREA.

Supplemental Safety and Health

NSN FOR TYPE I,METH D,LVL 1 OF MIL-I-25135.PER QPL-25135-15,TWO
EMULSIFIERS E-58A & E-58D ARE QUALIFIED ITEMS FOR TYPE I,METHOD
D,LEVEL 1 OF MIL-I-25135,REV D. THE MANUFACTURER MAY SUPPLY EITHER
ONE O F THESE EMULSIFIERS FOR THE NSN.THIS ENTRY DESCRIBES E-58A
EMULSIFIER. SEE PNI-B FOR E-58D DATA.

==
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:380F(193.3C

Spec Gravity:ABOUT 1.2

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT REDDISH PINK LIQUID. PRACTICALLY ODORLESS

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL

Stability Condition to Avoid:SOURCE OF HEAT/IGNITION. AVOID EXPOSURE TO
OXIDANTS.

Hazardous Decomposition Products:OXIDES OF CARBON (CAR

BON
MONOXIDE,CARBON DIOXIDE)

===== Disposal Considerations =====

Waste Disposal Methods:PER MANUFACTURER, THE WASTE CAN BE INCINERATED
OR DISPOSED OF AS EPA HAZARDOUS WASTE # D001,IGNITABLE WASTE, IN
FULL COMPLIANCE WITH ALL FEDERAL STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no ma
nner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.