View NSN Online: https://aerobasegroup.com/nsn/6850-01-268-6715 MET-L-CHEK COMPANY -- E-58D EMULSIFIER -- 6850-01-268-6715 ============= Product Identification ======================== Product ID:E-58D EMULSIFIER MSDS Date:06/08/1989 FSC:6850 NIIN:01-268-6715 MSDS Number: BGTCZ === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID STREET City:SANTA MONICA State:CA ZIP:90404-3770 Country:US Info Phone Num:213-450-1111 Emergency Phone Num:213-450-1111 CAGE:98733 = == Contractor Identification === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 City:SANTA MONICA State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733 ======= Composition/Information on Ingredients ======== Ingred Name: ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #: KW2975000

RTECS #:KW2975000 Fraction by Wt: 50.0%

Other REC Limits: NONE RECOMMENDED ACGIH TLV: C 50 PPM, VAPOR; 9394

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

====== Hazards Identificatio

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT MAY CAUSE SKIN AND EYE IRRITATION. INHALATION MAY CAUSE CNS DEPRESSION. INGESTION MAY BE HARMFUL (MODERATE SINGLE ORAL DOSE TOXICITY). CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CA RCINOGEN.

Effects of Overexposure: SKIN OR EYE IRRITATION, DRUNKENESS, NARCOSIS. Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN OR EYE DISORDERS.

First Aid:IN ALL CASES, GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES-FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN-FLUSH WITH WATER. INGESTED-IF CONSCIOUS, INDUCE VOMITING. GET MEDICAL ATTENTION. INHALED-RE MOVE TO FRESH AIR.

=======	========	Fire I	Fighti
ng Measures	=========	====	=====

Flash Point Method:PMCC Flash Point:232F,111C

Lower Limits:3.2

Extinguishing Media:WATER FOG, CARBON DIXOIDE, DRY CHEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures: NONE. DLA-HMIS: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL BUNKER GEAR.

Unusual Fire/Explosion Hazard:NONE.

=======================================	Accidental	Release	Measures	=============
---	------------	---------	----------	---------------

Spill Release Procedures:FLUSH WITH WATER. SOAK UP WITH ABSORBENT MATERIAL AND PLACE IN SEALED CONTAINERS FOR LATER DISPOSAL.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: KEEP IN SEALED CONTAINERS. WASH BEFORE EATING, DRINKING, OR USING TOILET. AVOID SKIN AND EYE CONTACT.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AI

R RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECO MMENDATIONS.

Ventilation:LOCAL EXHAUST OR MECHANICAL(GENERAL) TO MAINTAIN TLV OR BELOW TLV LIMITS.

Protective Gloves: CHEMICAL RESISTANT-NEOPRENE.

Eye Protection: SAFETY GLASSES OR SPLASH-PROOF GOGGLES

Other Protective Equipment: CHEMICAL RESISTANT APRON TO PREVENT CLOTHING/ SKIN CONTACT. DLA-HMIS: EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKI

NG, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

NSN FOR TYPE I,METH D,LVL 1 OF MIL-I-25135. PER QPL-25135-15,TWO EMULSIFIERS E-58A & E-58D ARE QUALIFIED ITEMS FOR TYPE I,METHOD D,LEVEL 1 OF MIL-I-25135,REV D. THE MANUFACTURER MAY SUPPLY EITHER ONE OF THESE EMULSIFIERS FOR THE NSN.THIS ENTRY DESCRIBES E-58D EMULSIFIER. SEE PNI-A FOR E-58A DATA.

=======================================	Physical/Chemical Properties	=======================================
HCC:N1		
Boiling Pt:B.P. T		
ext:380F,193C		
Vapor Pres:0.12		
Spec Gravity:1.2		

Solubility in Water:COMPLETE
Appearance and Odor:LIGHT REDDISH PINK LIQUID. PRACTICALLY ODORLESS

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL

Stability Condition to Avoid:TEMPERATURES AT OR ABOVE 775F. AVOID CONTACT WITH OXIDIZERS.

Hazardous Decomposition Products: CARBON MONOXIDE.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

	===== Dispos
al Considerations	==============

Waste Disposal Methods: CAN BE BURNED IF ALLOWED LOCALLY. OTHERWISE, DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. A

ny person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.