View NSN Online: https://aerobasegroup.com/nsn/6850-01-267-7988

Product ID: VP-30 PENETRANT MSDS Date:10/24/1986 FSC:6850 NIIN:01-267-7988 **MSDS Number: BGTHP** === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID STREET **City:SANTA MONICA** State:CA ZIP:90404-3770 Country:US Info Phone Num:213-450-1111 Emergency Phone Num:213-450-1111 CAGE:98733 === Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733 Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC CAS:64742-88-7 OSHA PEL:500 PPM ACGIH TLV:100 PPM Ingred Name:SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC CAS:64742-95-6 **OSHA PEL:500 PPM** ACGIH TLV:100 PPM

======= На

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE SLIGHT SKIN

IRRITATION;VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER
RESPIRATORY TRACT,AND CAUSES CNS DEPRESSION.

Effects of Overexposure:EYES/SKIN:LIQUID IS MINIMALLY IRRITATING TO THE

EYES AND SLIGHTLY IRRITATING TO THE SKIN.VAPORS CAUSE EYES
IRRITATION;INHALATION:VAPORS CAUS

E IRRITATION TO NOSE,THROAT AND

RESPIRATORY TRACT,AND CAUSE CNS DEPRESSION;INGESTION:MAY CAUSE
NAUSEA,GIDDINESS OR HEADACHE,AND POSSIBLE VOMITING.

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE,SKIN AND

RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EYES/SKIN:FLUSH WITH PLENTY OF RUNNING WATER.REMOVE CONTAMINATED CLOTHES,AND WASH SKIN WITH SOAP & WATER.GET MEDICAL

ASST IF IRRITATION PERSISTS; INHALATION: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATH ING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF REQUIRED.GET MED HELP IF NEEDED; INGESTION: DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS; GET MEDICAL ASSISTANCE IMMEDIATELY.

Flash Point Method:TCC Flash Point:140F/60C Lower Limits:1.0 Upper Limits:6.0 Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOAM; DO

NOT USE DIRECT STREAM OF WATER. Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRE SHOULD BE COOLED WITH WATER SPRAY TO PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RUPTURE CONTAINER.

Spill Release Procedures: ELIM IGNITION S

OURCES.WEAR APPROPRIATE PROTECTIVE CLOTHING & RESPIRATOR.DIKE & TRANSFER LIQ TO A SALVAGE TANK.SOAK UP RESIDUE WITH ABSORBENT CLAY,SAND OR OTHR MATL.PLACE RAGS & ABSORBED WASTE MATERL I N COVERED NON-LEAKING CONTAINERS.
======================================
Handling and Storage Precautions: KEEP AWAY FROM HEAT/IGNITION SOURCES. STORE IN DRY,COOL,& VENTILATED LOCATION.DO NOT STORE NEAR OXIDIZING MATERIAL. AVOID PHYSICAL DAMAGE TO CANS. Other Prec
autions:MINIMIZE SKIN CONTACT.KEEP CONTAINERS CLOSED WHEN NOT IN USE.USE WITH ADEQUATE VENTILATION;AVOID PROLONGED BREATHING OF VAPORS.
======================================
Respiratory Protection: IF EXPOSURE EXCEEDS TLV, USE NIOSH APPRVD RESPIRATOR TO PREVENT OVEREXPOSURE. Ventilation: PER MANUFACTURER, PROVIDE LOCAL EXHAUST, OR MECHANICAL (GENERAL) VENTILATION TO MAINTAIN TLV. Protective Gloves: CHEMICAL RESISTANT. Eye Protection: GOGGLES. Other Protect ive Equipment: EYE WASH FOUNTAINS AND SAFETY SHOWERS. Work Hygienic Practices: WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITES; MINIMIZE SKIN CONTACT. Supplemental Safety and Health NSN FOR TYPE II METHOD C OF MIL -1-25135 REVISION "D": PER
NSN FOR TYPE II,METHOD C OF MIL-I-25135,REVISION "D";PER QPL-25135-15,THE QUALIFIED PRODUCTS OF MET-L-CHEK ARE VP-30 AND VP-31A PENETRANTS FOR TYPE II,METHOD C. THIS ENTRY DESCRIBES:VP-30 PENETRANT; M FR MAY SUPPLY EITHER VP-30 OR VP-31A UNDER THIS NSN.
=========

HCC:F4 Boiling Pt:B.P. Text:368-415F Spec Gravity:0.8 Evaporation Rate & amp; Reference: