

HOCKING INTERNATIONAL CHEMICAL CORP. -- MIL-C-10578;CORROSION REMOVING COMPOUND
-- 6850-00-926-5298

===== Product Identification =====

Product ID:MIL-C-10578;CORROSION REMOVING COMPOUND

MSDS Date:12/28/1988

FSC:6850

NIIN:00-926-5298

MSDS Number: BGTKL

=== Responsible Party ===

Company Name:HOCKING INTERNATIONAL CHEMICAL CORP.

Address:2121-HOOVER AVE

City:NATIONAL CITY

State:CA

ZIP:92050-6529

Coun

try:US

Info Phone Num:619-474-8457

Emergency Phone Num:619-474-8457

CAGE:60930

=== Contractor Identification ===

Company Name:HOCKING INTERNATIONAL CHEMICAL CORP

Address:2121 HOOVER AVE

Box:City:NATIONAL CITY

State:CA

ZIP:92050

Country:US

Phone:619-474-8457

CAGE:60930

===== Composition/Information on Ingredients =====

Ingred Name:PHOSPHORIC ACID (SARA III)

CAS:7664-38-2

RTECS #:TB6300000

Fraction by Wt: 30.0%

OSHA PEL:1 MG/M3/3 STEL

ACGIH TLV:1 MG/M3/3 STEL; 9192

EPA Rpt Qty

:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:WATER SOFTNERS

Ingred Name:ALKALINE BUILDERS

Ingred Name:SURFACTANTS (NOT SPECIFIED)

Ingred Name:INHIBITORS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:CORROSIVE TO ALL BODY
TISSUES;SEVERE BURNS,IRRITATION TO EYES AND SKIN;IRRITATION OF
NOSE,THROAT AND RESPIRATORY TRACT;INGESTION MAY CAUSE G.I.
IRRITATION.CHRONIC:NO
DATA IS GIVEN.
Effects of Overexposure:SEE HEALT HAZARDS DATA.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR ABOUT 15 MINUTES;CONSULT A
PHYSICIAN. SKIN:WASH THOROUGHLY USING PLENTY OF WATER;SEEK MEDICAL
HELP IF NEEDED. INHALATION:REMOVE TO FRESH AIR;SUPPLY OXYGEN IF
NEEDED. INGESTION:DO NOT INDUCE VOMITING;CALL A PHYSICIAN
IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:N
ONE
Extinguishing Media:DRY CHEMICAL,FOAM,CO*2,WATER SPRAY.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:TOXIC VAPORS ON DECOMPOSITION;WITH METAL
HYDROCARBON MAY BE PRODUCED WHICH MAY FORM FLAMMABLE MIXTURES WITH
AIR.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE
LIQUID;USE SODA ASH;DILUTE WITH WATER AND RECOVER FOR PROPER
DI

SPOSAL.

Neutralizing Agent:SODA ASH.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA;PROTECT CONTAINERS FROM LEAKAGE OR PHYSICAL DAMAGE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR AN ACID MIST/VAPOR IF ABOVE TLV/PEL.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:RUBBER.

Eye Protection:

CHEMICAL GOGGLES OR FACE SHIELD.

Other Protective Equipment:RUBBER BOOTS,EYE-WASH FACILITIES.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPOR/MIST.WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:C1

Boiling Pt:B.P. Text:275F/135C

Vapor Pres:5.68

Spec Gravity:1.25

Solubility in Water:100%;COMPLETE

Appearance and Odor:LIGHT AMBER COLOR WITH MILD FRAGRANT ODOR.

Percent Volatile

s by Volume:60.0

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

MILD STEEL,COPPER,BRASS AND BRONZE.

Stability Condition to Avoid:WILL FREEZE LOW TEMPERATURES-0.5F.

Hazardous Decomposition Products:OXIDES OF PHOSPHORUS.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this

information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.