

GC ELECTRONICS CO,SUB OF HOUSEHOLD INTER. CORP -- 10-5303,MAGNETIC HEAD CLEANER --
5850-00-201-1136

===== Product Identification =====

Product ID:10-5303,MAGNETIC HEAD CLEANER

MSDS Date:12/02/1986

FSC:5850

NIIN:00-201-1136

MSDS Number: BGVKJ

=== Responsible Party ===

Company Name:GC ELECTRONICS CO,SUB OF HOUSEHOLD INTER. CORP

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

E

mergency Phone Num:815-968-9661

CAGE:EO032

=== Contractor Identification ===

Company Name:GC ELECTRONICS CO,SUB OF HOUSEHOLD INTERNATIONAL C

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Phone:815-968-9661

CAGE:EO032

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL

ZIP:61105

Country:US

Phone:815-968-9661

CAGE:72653

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000
Fraction by Wt: 100%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE DIZZINESS,NAUSEA,EYE
IRRITATION.
Effects of Overexposure:SEE "HEALTH HAZARDS"
Medical Cond Aggravated by Exposure:NONE STATED.

=====
===== First Aid Measures =====
=====

First Aid:EYE:FLUSH WITH WATER FOR AT LEAST 15 MINUTES; SKIN:WASH WITH
SOAP & WATER; INHALE:REMOVE TO FRESH AIR; INGEST:INDUCE VOMITING,
CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:CC
Flash Point:54F/12.2C
Lower Limits:3.3
Upper Limits:19
Extinguishing Media:CO*2,FOAM
Fire Fighting Procedures:VENTILATE AREA WELL. USE SELF-CONTAINED
BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE KNOWN.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:SMALL QUANTITIES WILL EVAPORATE QUICKLY.PICK
UP WITH INERT ABSORBENT.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:STORE IN COOL AREA, AWAY FROM IGNITION
SOURCES OR STRONG OXIDIZERS.
Other Precautions:AVOID PROLONGED BREATHING OF FUMES.

=====
===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:IF TLV IS EXCEEDED, USE NIOSH

/MSHA APPROVED
RESPIRATOR.

Ventilation:LOCAL EXHAUST.

Protective Gloves:NOT ORDINARILY REQUIRED.

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:PRODUCT NO. 10-5303

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=73.9C, 165.F

Vapor Pres:40

Vapor Density:1.59

Spec Gravity:.812

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR,COLORLESS,ALCOHOL ODOR.

Percent Volatiles by Volume:100

===== Stability
and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:AVOID IGNITION SOURCES.

Hazardous Decomposition Products:CO,CO*2.

===== Disposal Considerations =====

Waste Disposal Methods:AUTHORIZED INCINERATOR.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America
in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.