

EXXON CO USA;A DIV OF EXXON CORP -- KEROSENE;PRODUCT CODE:055000-00700 --
9140-00-242-6748

===== Product Identification =====

Product ID:KEROSENE;PRODUCT CODE:055000-00700

MSDS Date:04/10/1986

FSC:9140

NIIN:00-242-6748

MSDS Number: BGVQM

=== Responsible Party ===

Company Name:EXXON CO USA;A DIV OF EXXON CORP

Address:800 BELL STREET

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Pho

ne Num:713-656-3424

Emergency Phone Num:713-656-3424

CAGE:KO806

=== Contractor Identification ===

Company Name:EXXON CO USA;A DIV OF EXXON CORP

Address:800 BELL STREET

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-3424

CAGE:KO806

Company Name:EXXON COMPANY U.S.A.

Address:Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

===== Composition/Information on Ingredients =====

Ingred Name:KEROSENE (ASTM GRA

DE 2-K)
CAS:8008-20-6
RTECS #:OA5500000
Fraction by Wt: 100.0%
Other REC Limits:100PPM

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL RAT >5G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND
RESPIRATORY TRACT,HEADACHE,DIZZINESS,ANESTHETIC EFFECTS AND CNS
EFFECTS. CHRONIC:IRRITATION AND DERMATITIS.
Explanation of Carcinogenicity:NO DATA AVAILABLE.
Effects of Overexposure:SEE HEALTH HAZARDS DATA.
Medical Condition Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH CLEAR WATER FOR ABOUT 15 MINUTES,CALL A
PHYSICIAN IF NEEDED. SKIN:WASH THOROUGHLY WITH SOAP AND WATER.
INHALATION:REMOVE TO FRESH AIR;CALL A PHYSICIAN IMMEDIATELY.
INGESTION:DO NOT INDUCE VOMITING;CALL A PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:100F/38C
Autoignition Temp:Autoignition Temp Text:410F
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:FOAM,WATER SPRAY,DRY CHEMICAL,CO*2.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.USE FULL PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:TOXIC VAPORS/MIST;OXIDES OF
CARBON,ALDEHYDES.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL

PROTECTION;REMOVE ALL
IGNITION SOURCES;CONTAIN FREE LIQUID IF POSSIBLE;USE SUITABLE INERT
ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED
AREA.KEEP AWAY FROM HEAT,OPEN FLAME,SPARKS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
VAPORS/MIST IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV (USE EXPLOSION PROOF
EQUIPMENT).

Protective Gloves:IMPERVIOUS.

Eye Protection:GOGGLES/SIDE SHIELDS.

Other Protective Equipment:APRON,EYE-WASH FOUNTAIN OR AS REQUIRED.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE
VAPORS/MIST WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.

P. Text:320-355F

Vapor Pres: