

NATIONAL WELDING ALLOYS, INC. -- 5356 ALUMINUM -- 3439-01-012-6661  
===== Product Identification =====

Product ID:5356 ALUMINUM  
MSDS Date:11/10/1986  
FSC:3439  
NIIN:01-012-6661  
MSDS Number: BGWFM  
=== Responsible Party ===  
Company Name:NATIONAL WELDING ALLOYS, INC.  
Address:1600 SOUTH CANAL STREET  
City:PITTSBURGH  
State:PA  
ZIP:15215  
Country:US  
Info Phone Num:412-781-4255  
Emergency Phone Num:412-781-425  
5  
CAGE:0ACE2  
=== Contractor Identification ===  
Company Name:NATIONAL WELDING ALLOYS INC  
Address:1600 SOUTH CANAL STREET  
Box:City:PITTSBURGH  
State:PA  
ZIP:15215-2624  
Country:US  
Phone:412-781-4255  
CAGE:0ACE2

===== Composition/Information on Ingredients =====

Ingred Name:ALUMINUM (SARA III)  
CAS:7429-90-5  
RTECS #:BD0330000  
Fraction by Wt: 93-94%  
Other REC Limits:NONE  
OSHA PEL:15MG/M3 DUST/5 FUME  
ACGIH TLV:10MG/M3 DUST; 9192

Ingred Name:MAGNESIUM  
CAS:7439-95-4  
RTECS #:OM2100000  
O

ther REC Limits:NONE

Ingred Name:IRON  
CAS:7439-89-6  
RTECS #:NO4565500  
Fraction by Wt: 0.4%  
Other REC Limits:NONE  
OSHA PEL:10MG/M<sup>3</sup>(FE\*2O\*3)  
ACGIH TLV:15MG/M<sup>3</sup>(FE\*2O\*3)

Ingred Name:SILICON  
CAS:7440-21-3  
RTECS #:VW0400000  
Fraction by Wt: 0.25%  
Other REC Limits:NONE  
OSHA PEL:15 MG/M<sup>3</sup> TDUST  
ACGIH TLV:10 MG/M<sup>3</sup> TDUST; 9293

Ingred Name:TITANIUM  
CAS:7440-32-6  
RTECS #:XR1700000  
Fraction by Wt: .06-20%  
Other REC Limits:NONE  
OSHA PEL:10MG/M<sup>3</sup>(TIO\*2)  
ACGIH TLV:10MG/M<sup>3</sup>(TIO\*2)

Ingred Name:CHROMIUM (SARA  
III)  
CAS:7440-47-3  
RTECS #:GB4200000  
Fraction by Wt: .05-.20%  
Other REC Limits:NONE  
OSHA PEL:1 MG/M<sup>3</sup>  
ACGIH TLV:0.5 MG/M<sup>3</sup>; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:MANGANESE (SARA III)  
CAS:7439-96-5  
RTECS #:OO9275000  
Other REC Limits:NONE  
OSHA PEL:(C) 5 MG/M<sup>3</sup> DUST  
ACGIH TLV:5 MG/M<sup>3</sup> DUST 9293

Ingred Name:COPPER (SARA III)  
CAS:7440-50-8  
RTECS #:GL5325000  
Fraction by Wt: 0.1%  
Other REC Limits:NONE  
OSHA PEL:0.1MG/M<sup>3</sup> FUME/1 DUST  
ACGIH TLV:0.2MG/M<sup>3</sup> FUME; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt

Qty:5000 LBS

Ingred Name:ZINC (SARA III)

CAS:7440-66-6

RTECS #:ZG8600000

Fraction by Wt: 0.1%

Other REC Limits:NONE

OSHA PEL:10 MG ZNO/M3

ACGIH TLV:10 MG ZNO/M3; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:OTHER TOTAL

Fraction by Wt: 0.15%

Other REC Limits:NONE

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACU

TE:METALLIC TASTE,NAUSEA,TIGHTNESS

OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE,THROAT.

CHRONIC:EXCESSIVE LEVELS MAY CAUSE BRONCHIAL ASTHMA,LUNG

FIBROSIS,PNEUMOCONIOSIS.

Explanation of Carcinogenicity:CHROMIUM IS LISTED UNDER NTP AND IARC.

Effects of Overexposure:METALLIC TASTE, NAUSEA, TIGHTNESS OF CHEST,

FEVER, DIZZINESS, DRYNESS, IRRITATION OF EYES, NOSE AND THROAT.

Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY  
OR ALLERGIC CONDITIONS.H

HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG  
SMOKERS.

=====  
First Aid Measures  
=====

First Aid:REMOVE FROM EXPOSURE AND OBTAIN PROMPT MEDICAL ATTENTION. IF  
NOT BREATHING,GIVE CPR.IF UNCONSCIOUS,GIVE OXYGEN. EMPLOY FIRST AID  
TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:FIR

E FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:WELDING ARCS AND SPARKS CAN IGNITE COMBUTIBLE PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPRIATE DOT APPROVED DISPOSAL CONTAINER.

===== Handling and Storage

e =====

Other Precautions:TRAIN WELDER TO KEEP HIS OUT OF THE FUMES. MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:LOCAL EXHAUST TO MAINTAIN BELOW TLV.

Protective Gloves:WELDER'S GLOVES.

Eye P

rotection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH,ARM PROTECTOR,APRON,HAT,SHOULDER PROTECTION.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKE,USING SANITARY FACILITIES.

Supplemental Safety and Health  
NONE.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:WELDING ROD.NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: FUMES OF METALS AND METALS  
OXIDES, CO, NO\*2, O\*3.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF FUMES, FLUX OR WELD GRINDING RESIDUE  
FROM THE WORK AREA OR FROM FILTERS IAW ALL APPLICABLE FEDERAL, STATE  
AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the

Department

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.