

PARKER-HANNIFIN CORP SEAL GROUP O-RING DIVISION -- SUPER-O-LUBE -- 9150-01-132-8871
===== Product Identification =====

Product ID: SUPER-O-LUBE

MSDS Date: 06/03/1998

FSC: 9150

NIIN: 01-132-8871

MSDS Number: BGWQZ

=== Responsible Party ===

Company Name: PARKER-HANNIFIN CORP SEAL GROUP O-RING DIVISION

Address: 2360 PALUMBO DRIVE

Box: 11751

City: LEXINGTON

State: KY

ZIP: 40512

Country: US

Info Phone Num: 606-26

9-2351

Emergency Phone Num: 606-269-2351

CAGE: 02697

=== Contractor Identification ===

Company Name: DBR INDUSTRIES, INC

Address: 18 PENNS TRL

Box: City: NEWTON

State: PA

ZIP: 18940-1813

Country: US

Contract Num: SP0450-99-M-B277

CAGE: 1K697

Company Name: EMULTEC INDUSTRIAL PRODUCTS INC

Address: 1150 HAYDEN DR SUITE 100

Box: City: CHARROLLTON

State: TX

ZIP: 75006

Country: US

Phone: 972-417-1288

Contract Num: SP0450-00-M-C175

CAGE: 0WA27

Company Name: PARKER-HANNIFIN CORP SEAL GROUP O-RING DIVISION

Address: 2360 PALUMB

O DRIVE
Box:11751
City:LEXINGTON
State:KY
ZIP:40509
Country:US
Phone:606-269-2351
CAGE:02697
Company Name:VALUE INDUSTRIES INC
Address:2000 AVE G SUITE 802
Box:260961
City:PLANO
State:TX
ZIP:75026-0961
Country:US
Phone:214-596-9398
CAGE:0KT99

=====
Composition/Information on Ingredients
=====

Ingred Name:DIMETHYL SILOXANE POLYMER
CAS:63148-62-9
RTECS #:JT6484500
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC
50 Mixture:NO DATA PROVIDED BY RESPONSIBLE PARTY.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE; MAY CAUSE TEMPORARY EYE
DISCOMFORT. CHRONIC: NO DATA PROVIDED BY RESPONSIBLE PARTY.
Explanation of Carcinogenicity:RESPONSIBLE PARTY LISTED NO INFORMATION
ABOUT THE CARCINOGENICITY OF THIS MATERIAL. HMIS DOES NOT EXPECT IT
TO BE CARCINOGENIC.
Effects of Overexposure:EYE IRRITATION.
Medica
I Cond Aggravated by Exposure:NO DATA PROVIDED BY RESPONSIBLE
PARTY.

=====
First Aid Measures
=====

First Aid:FLUSH WITH WATER.

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:=321.1C, 610.F
Extinguishing Media:CARBON DIOXIDE OR FOAM.
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING
CHEMICALS..
Unusual Fire/Exp

losion Hazard:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN SPILLED MATERIAL FOR SALVAGE OR PROPER DISPOSAL.

Neutralizing Agent:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUTIONS.

Other Precautions:AT ELEVATED TEMPERATURES, THIS PRODUCT IS SENSITIVE TO CONTAMINATION. IF THIS PRODUCT BECOMES CONTAMINATED WITH STRONG ACIDS, BASES, SOME METALLIC COMPOUNDS OR OXIDIZING AGENTS, THE FLASH POINT AND VI SCOSITY MAY CHANGE AND SHOULD BE REDETERMINED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:N/A.

Ventilation:MECHANICAL(GENERAL): RECOMMENDED.

Protective Gloves:PROTECTIVE GLOVES RECOMMENDED.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:N/A.

Work Hygienic Practices:MFR: N/P. HMIS:USE GOOD INDUSTRIAL HYGIE NE

PRACTICE. AVOID UNNECESSARY EXPOSURE. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>148.9C, 300.F

Melt/Freeze Pt:=-36.1C, -33.F

M.P/F.P Text:POUR POINT

Vapor Pres: