DOW CORNING CORP -- 93-118 CURING AGENT, PART A -- 8030-01-033-1530

Product ID:93-118 CURING AGENT, PART A MSDS Date:08/17/1990 FSC:8030 NIIN:01-033-1530 Kit Part:Y MSDS Number: BGWSL === Responsible Party === Company Name: DOW CORNING CORP Address:3901 SOUTH SAGINAW ROAD Box:997 City:MIDLAND State:MI ZIP:48640 Country:US Info Phone Num:517-496-5900 **Emergency Phone** Num:517-496-5900 Preparer's Name: JACK L. SHENEBERGER CAGE:5D028 === Contractor Identification === Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028 Company Name: DOW CORNING CORP Address:2200 W SALZBURG RD Box:City:AUBURN State:MI ZIP:48611 Country:US Phone:517-496-4388 CAGE:71984

Ingred Name: DIMETHYL, METHYL HYDROGEN SILO

XANE COPOLYMER CAS:68037-59-2 Fraction by Wt: 11% Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE EFFECTS: DIRECT CONTACT WITH EYES MAY CAUSE TEMPORARY DISCOMFORT. CHRONIC EFFECTS:NONE KNOWN. Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN. Effects of Overexposure: EYES: MAY CAUSE TEMPORARY DISCOMFORT. SKIN: SEVERAL, PROLONGED EXPOSURE (HOURS) MAY CAUSE SLIGHT IRRITATION. INHALATION: NO IRRITATION TO NOSE OR THROAT EXPECT-ED. NO INJURY IS LIKELY FROM RELATIVELY SHORT EXPOSURE. ORAL: AMOUNTS TRANS-FERRED TO MOUTH BY FINGERS DURING NORMAL USE SHOULD NOT CAUSE INJURY. Medical Cond Aggravated by Exposure: MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. _____ First Aid: EYES: FLUSH WITH WATER. SKIN: WIPE OFF AND FLUSH WITH INHALATION: NO PROBLEM. ORAL: NO PROBLEM: WATER. Flash Point Method:CC Flash Point:>212F.>100C Autoignition Temp: Autoignition Temp Text: UNKNON Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHE N FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard: FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS. Spill Release Procedures: USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL. Handling and Storage Precautions: STORE IN COOL, DRY, WEL

L VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE, HEAT, IGNITION SOURCES AND INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED.

Other Precautions: PRODUCT EVOLVES MINUTE AMOUNTS OF HYDROGEN GAS. DO NOT REPACKAGE OR STORE IN UNVENTED CONTAINERS. AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPIATE FOR EXPOSURE OF CON CERN IF

EXPOSURE LEVELS ARE EXCEEDED. Ventilation:MECHANICAL (GENERAL) VENTILATION RECOMMENDED. Protective Gloves:NONE SPECIFIED BY MANUFACTURER. Eye Protection:SAFETY GLASSES, AS A MINIMUM Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health KEX1:N1_THIS IS PART A OF A 2-PART KIT FOR PART B. SEE PNLB_SAME

KEY1:N1. THIS IS PART A OF A 2-PART KIT FOR PART B, SEE PNI B, SAME NSN. CONTACT WITH WATE

R, SOME METALS, ACIDS OR BASES MAY LIBERATE FLAMMABLE, EXPLOSIVE HYDROGEN GAS.

HCC:N1 Vapor Pres: