

INDUSTRIAL FLOOR FINISHES -- LIQUID POLISH -- 7930-00-266-7142

=====  
Product Identification  
=====

Product ID:LIQUID POLISH  
MSDS Date:05/19/1987  
FSC:7930  
NIIN:00-266-7142  
MSDS Number: BGXMR  
=== Responsible Party ===  
Company Name:INDUSTRIAL FLOOR FINISHES  
Address:605 SPRING STREET  
City:BEDFORD  
State:MA  
ZIP:01730  
Country:US  
Info Phone Num:508-667-5161  
Emergency Phone Num:508-667-5161 OR LOCAL POISON  
CENTER  
Preparer's Name:T. PITROFF  
CAGE:INDUS  
=== Contractor Identification ===  
Company Name:INDUSTRIAL FLOOR FINISHES  
Address:605 SPRINGS RD  
City:BEDFORD  
State:MA  
ZIP:01730  
Country:US  
Phone:1-617-667-5161  
CAGE:INDUS

=====  
Composition/Information on Ingredients  
=====

Ingred Name:STODDARD SOLVENT  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 17%  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM; 9293

=====  
Hazards Identification  
=====

Routes of Entry:

Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards Acute and Chronic: ACUTE: PRIMARY EYE AND SKIN IRRITANT  
WITH CONTACT. CHRONIC: NOT SUFFICIENT DATA.  
Effects of Overexposure: HEADACHE, DIZZINESS AND NAUSEA.

=====  
===== First Aid Measures =====

First Aid: EYES: FLUSH WITH WATER; SKIN: WASH WITH SOAP AND WATER, APPLY  
SKIN CREAM. INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING, CALL  
PHYSICIAN. INGESTION: DRINK WATER OR MILK, DO NOT INDUCE VOMITING.

CALL POISON CONTROL.

=====  
===== Fire Fighting Measures =====

Flash Point Method: TCC  
Flash Point: 104F-40C  
Lower Limits: 0.8  
Upper Limits: 6.0  
Extinguishing Media: FOAM, CO2, DRY CHEMICAL.  
Fire Fighting Procedures: WATER MAY BE USED TO COOL CONTAINERS TO  
PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION.  
Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT. CLOSED CONTAINERS MAY  
EXPLODE IF EXPOSED TO EXTREME HEAT.

=====  
===== Accidental Release Measures =====

=====

Spill Release Procedures: REMOVE SOURCES OF IGNITION, SPRINKLE WITH  
ABSORBENT. FOG WITH WATER, FLUSH OR SCRAPE INTO RETAINING AREA OR  
CONTAINER. INCREASE VENTILATION. AVOID BREATHING VAPORS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS AND OPEN  
FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED  
CONTACT. KEEP CONTAINER CLOSED.  
Other Precautions: AVOID STATIC BUILD-UP. KEEP AWAY  
FROM CHILDREN.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: SELF CONTAINED BREATHING APPARATUS FOR  
CONCENTRATIONS ABOVE TLV.  
Ventilation: LOCAL AND MECHANICAL EXHAUST FROM LOWER LEVELS.  
Protective Gloves: USE RUBBER GLOVES.  
Eye Protection: SAFETY GLASSES.  
Other Protective Equipment: EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM.  
Supplemental Safety and Health  
NONE

=====  
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Te

xt:215F

Vapor Pres:2

Vapor Density:3.8

Spec Gravity:1.1

Evaporation Rate & Reference: