Product ID:00410 AVJET A MSDS Date:09/10/1986 FSC:9130 NIIN:00-359-2026 MSDS Number: BGXQY === Responsible Party === Company Name: TEXACO INC. Box:509 City:BEACON State:NY ZIP:12508-0509 Country:US Info Phone Num:914-831-3400 Emergency Phone Num:914-831-3400 CAGE:38431 === Contractor Identification === Company Name :DIGITAL CONTROL SYSTEMS INC Address:3160 GRAND MARAIS E Box:City:WINDSOR, N8W 4W5 State:ON Country:CN Phone:NONE CAGE:38431 **Company Name: TEXACO INC** Box:509 **City:BEACON** State:NY ZIP:12508-0509 Country:US Phone:914-831-3400 CAGE:7B131 Company Name: TEXACO REFINING AND MARKETING INC Address:1111 RUSK ST Box:City:HOUSTON State:TX ZIP:77002-3310 Country:US Phone:713-650-5206 CAGE:2R503

Ingred Name:KEROSINE CAS:8008-20-6 RTECS #:SE 7548500 Fraction by Wt: 100% Other REC Limits:HMIS:100 PPM/5 MG/M3 OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

LD50 LC50 Mixture:ORAL RAT LD50 IS >25 GRAM/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PRODUCT IS A MILD IRRITANT. MOST HAZARDOUS EXPOSURE;EXPOSURE IS TO AIRBORN MIST OR OTHER ASPIRATION OF LIQU ID INTO LUNGS. PROLONGED/REPEATED OVEREXPOSURE HAS CAUSED KIDNEY DAMAGE IN MICE. Explanation of Carcinogenicity:STUDIES INDICATE THAT REPEATED OVER EXPOSURES WITHOUT CLEANSING CAUSE SKIN CANCER IN MICE. THEREFORE WASH OFTEN. Effects of Overexposure:EYE:MILD IRRITATION. SKIN:DRYING,DEFATTING WITH PROLONGED/REPEATED CONTACT. INHALED:HEADACHE,NAUSEA,CONFUSION, DROWINESS. ASPIRATION OF LIQUID MAY CAUSE CHEMICAL PNEUMONITIS. INGESTED:G/ I IRRITATION, NAUSEA,POSSIBLE VOMITING.

Medical Cond Aggravated by Exposure:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:DO N OT INDUCE VOMITING. GIVE 2 LARGE GLASSES OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. DOCTOR TO ORDER VOMITING. N

OTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE, SEE A DOCTOR.

Flash Point Method:TCC Flash Point:120F/49C Autoignition Temp:Autoignition Temp Text:480F Lower Limits:0.58 Upper Limits:4.45 Extinguishing Media:ACCORDING TO NFPA GUIDE 49, COMBUSTABLE LLIQUID FIRES MAY BE EXTINGUISHED BY WATER SPRAY, DRY CHEMICAL, FOAM OR CO*2. Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &

FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: VENTILATE AREA. AVOID BREATHING VAPORS. USE SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR MASK FOR LARGE SPILLS IN CONFINED AREA. CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP. Neutralizing Agent :NONE

Handling and Storage Precautions: STORE IN COOL AREA AWAY FROM OXIDIZERS AND IGNITION SOURCES. DETACHED STORAGE PREFERRED. GROUND CONTAINERS DURING TRANSFER.

Other Precautions:WASTE CLASSIFICATION OF THIS PRODUCT IN ITS UNUSED FORM IS D001. * "EMPTY" CONTAINERS MAY CONTAIN RESIDUE SND/OR FUMES WHICH ARE EXPLOSIVE. DO NOT CUT,WELD,ETC.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR SCBA FOR ENTRY INTO TANKS OR CONFINED SPACES OR HANDLING LARGE SPILLS. SEE 29 CFR 1910.134 FOR REGULATION S PERTAINING TO RESPIRATOR USE.
Ventilation: NORMAL ROOM VENTILATION IS SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST IF PEL/TLV IS EXCEEDED.
Protective Gloves: NO INFORMATION GIVEN ON MSDS BY SUPPLIER
Eye Protection: SPLASH GOGGLES. OR FACE SHIELD
Other Protective
Equipment: WASH EXPOSED SKIN SEVERAL TIMES DAILY AND LAUNDER SOILED CLOTHING REGULARLY.
Work Hygienic Practices: USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT.
Supplemental Safety and Health NONE

HCC:F4 Boiling Pt:B.P. Text:515F/269C Vapor Pres: