View NSN Online: https://aerobasegroup.com/nsn/6850-00-274-5421

Product ID:FO 425 A MSDS Date:08/01/1988 FSC:6850 NIIN:00-274-5421 MSDS Number: BGZZK === Responsible Party === Company Name: FINE ORGANICS CORP Address:205 MAIN ST Box:687 City:LODI State:NJ ZIP:07644-0687 Country:US Info Phone Num:(800) 526-7480 Emergency Phone Num: (800) 526-7480 Preparer's Name: J.I. GREENBERG CAGE:84519 === Contractor Identification === **Company Name: FINE ORGANICS CORPORATION** Address:205 MAIN ST Box:687 City:LODI State:NJ ZIP:07644-0687 Country:US CAGE:84519 Ingred Name: HYDROTREATED LIGHT DISTILLATE, PETROLEUM CAS:64742-47-8 Fraction by Wt: 100% Other REC Limits:300 PPM (MFR) **OSHA PEL:500 PPM** ACGIH TLV:100 PPM 

Routes of Entry: Inhalation:YES Sk

in:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: MAY HAVE RESULTS MILD DEPRESSION TO RESPIRATORY IRRITATION. SKIN: PROLONGED CONTACT MAY LEAD TO EXTRACTION OF NATURAL OILS W/RESULTANT IRRITATION. EYE: WILL CAUSE IRRITATION. INGESTION: MAY AFFECT KIDNEYS. HEALTH RISKS WHICH VARY FROM PERSON TO PERSON. Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: MAY HAVE RESULTS MILD DEPRESSION TO
RESPIRATORY IRRITATION. SKIN: PROLONGED CONTACT MAY LEAD TO EXTRACTION OF NATURAL OILS W/RESULTANT IRRITATION. EYE: WILL CAUSE IRRITATION. INGESTION: MA Y AFFECT KIDNEYS.
======================================
First Aid:INHALATION: REMOVE FROM EXPOSURE. ADMINISTER ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. EYE: FLUSH W/WATER FOR 15 MIN. INGESTION: DON'T INDUCE VOMITING. GIVE PLENTY OF WATER. IF CONTACTED, REMOV E CONTAMINATED CLOTHES/WAS H AREA WITH PLENTY OF WATER. SEEK MEDICAL ATTENTION.
======================================
Flash Point Method:COC Flash Point:180F Extinguishing Media:FOAM, DRY CHEMCIAL, CO2, WATER SPRAY/FOG Fire Fighting Procedures:USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREA. COOL EXPOSED CONTAINRS W/WATER. Unusual Fire/Explosion Hazard:DON'T STORE & MIX WITH STRONG OXIDANTS. COMBUSTION LIQUID.
======================================
Spill Release Procedures:REMOVE IGNITION SOURCES. RECOVER FREE LIQUID & ADD ABSORBENT TO SPILL AREA. AVOID BREATHING VAPORS. VENTILATE ENCLOSED SPACES.
======================================
Ventilation:LOCAL EXHAUST: FACE VELOCITY >60FPM/MECHANICAL: USE EXPLOSION PROOF EQUIPMENT. Protective Gloves:NEOPRENE Eye Protection:SPLASH GOGGLES Supplemental Safety and Health
======================================
HCC:V4

Boi

ling Pt:B.P. Text:401-409F Vapor Pres:5 Spec Gravity:0.79 Evaporation Rate & amp; Reference:(N-BU AC = 1): 0.1 Solubility in Water:NEGLIGIBLE Appearance and Odor:WATER WHITE-ODORLESS Percent Volatiles by Volume:100%

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS LIKE LIQUID CHLORINE, CONCENTRATED OXYGEN SODIUM/CALCIUM HYPOCHLORITE.
Hazardous Decomposition Products:FUMES, SMOKE & CO IN CASE OF INCOMPLETE COMB
USTION.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/ALL LOCAL, STATE, & FEDERAL REGULATIONS, DISPOSAL RECOMMENDATIONS APPLY TO THE ORIGINAL MATERIAL & ITS CONTAINER, NOT ANY MATERIALS WHICH AREA WASTE BY PRODUCTS OF THE USER' S OPERATION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United State

s of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.