

DEXTER CORPORATION -- STATIC CONDITIONER -- 8030-01-046-5065

=====  
Product Identification  
=====

Product ID:STATIC CONDITIONER

MSDS Date:10/03/1987

FSC:8030

NIIN:01-046-5065

MSDS Number: BHBCN

=== Responsible Party ===

Company Name:DEXTER CORPORATION

Address:31500 HAYMAN

City:HAYWARD

State:CA

ZIP:94544

Info Phone Num:(415) 796-4972

Emergency Phone Num:(415) 471-7171

Preparer's Name:S. MORRIS

CAGE:

79436

=== Contractor Identification ===

Company Name:CROWN

Box:350

City:GREENVILLE

State:SC

ZIP:29606

Country:US

Phone:803-277-1870

CAGE:06367

Company Name:DEXTER CORP DEXTER ELECTRONIC MATERIALS

Address:15051 E DON JULIAN RD

Box:City:INDUSTRY

State:CA

ZIP:91746-1282

Country:US

Phone:626-968-6511

CAGE:79436

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HYDROTREATED LIGHT DISTILLATE, PETROLEUM

CAS:64742-47-8

Fraction by Wt: 20-30%

Other REC Limits:300 PPM (MFR)

)  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: RESPIRATORY TRACT  
IRRITATION, HEADACHE, DIZZINESS & DROWSINESS. SKIN/EYE: IRRITATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INHALATION: RESPIRATORY TRACT IRRITATION,  
HEADACHE, DIZZINESS & DROWSINESS. SKIN/EYE  
: IRRITATION.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. EYE: FLUSH IMMEDIATELY  
W/LARGE AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. SKIN:  
WASH W/SOAP & WATER. REMOVE/WASH CONTAMINATED CLOTHING. INGESTION:  
DRINK WATER.

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:102F  
Lower Limits:1.0%  
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL, CO2

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS, VENTILATE AREA & REMOVE W/INERT ABSORBANT &  
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINER SHOULD BE GROUNDED WHEN  
POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF FEW INCHES. KEEP  
CONTAINERS CLOSED WHEN NOT IN USE.  
Other Precautions:MAKE SURE THE DRUM IS

COMPLETELY EMPTY BEFORE

ATTEMPTING TO WELD/BRAZE. DRUM SHOULD BE INDUSTRIALLY CLEANED PRIOR TO REUSE. DON'T FLAME CUT/BRAZE/WELD W/O A NIOSH APPROVED RESPIRATOR/APPROPRIATE VENTILATION. DON'T TAKE INTERNALLY.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR LINE TYPE RESPIRATORS/HOODS FOR ENCLOSED & CONFINED AREAS. AIR PURIFYING RESPIRATORS MAY BE USED FOR OTHER AREAS.

Ventilation:PROVIDE MECHANICAL/LOCAL EXHAUST VENTILATION TO KEEP AIR

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO & OXIDES OF NITROGEN. MAY PRODUCE HAZARDOUS FUMES WHEN HEATED.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.