

NILES CHEMICAL PAINT COMPANY -- N-2000A BLACK CAMO HS TYPE IV -- 8010-01-260-0913

=====  
Product Identification  
=====

Product ID:N-2000A BLACK CAMO HS TYPE IV

MSDS Date:08/08/1989

FSC:8010

NIIN:01-260-0913

Kit Part:Y

MSDS Number: BHBFH

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT COMPANY

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-

3377 (INFORMATION)

Emergency Phone Num:219-236-5856 (24 HOURS)

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POLYESTER RESIN

Fraction by Wt: 14%

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475

000

Fraction by Wt: 10%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BARIUM SULFATE

CAS:7727-43-7

RTECS #:CR0600000

Fraction by Wt: 9%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:PM ACETATE

(VAPOR PRESSURE 3.7 MM @ 20C)

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 7%

Ingred Name:METHYL PROPYL KETONE (2-PENTANONE)

CAS:107-87-9

RTECS #:SA7875000

Fraction by Wt: 5%

OSHA PEL:200 PPM/250 STE

L

ACGIH TLV:200 PPM/250STEL;9192

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 5%

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 2%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:VOC. ORGANIC CMPD 3.83 LB/GAL LESS WATER & NPRS\* 480 G/L

LESS WATER VOC.10.59 LB/GAL SOLIDS 1236 G/L SOLIDS CALCU  
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES:SEVERE IRRITATION,REDNESS,BLURRED  
VISION.SKIN:DEFATTING OF THE SKIN LEADINGTO DERMITIS.INHALE:CNS  
DEPRESSION,UNCONSCIOUSNESS,EVEN ASPHYXIATION.INGESTION:  
GASTROINTESTINAL IRRITATION, ABDOM  
INAL PAIN, NAUSEA, AND VOMITING.  
CHRONIC:NARCOSIS, COMA, INCOHERENCE, CORNEAL VACUOLIZATION,  
ANOREXIA.  
Effects of Overexposure:DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE,  
CONFUSION. TARGET ORGANS:RESPIRATORY  
SYSTEM, EYES, SKIN, CNS,LUNGS GI TRACT, BLOOD,LIVER, KIDNEYS.

===== First Aid Measures =====

First Aid:INHALE:MOVE VICTIM TO FRESH AIR AT ONCE. IF BREATHING HAS  
STOPPED GIVE CPR.SKIN:IMMED FLUSH W/WATER.REMOVE CONTAMINATED  
CLOTHING AND FLUSH THE SKIN W/ WATER. EYE: FLUSH WITH WATER FOR  
15 MIN. LIFTING EYELIDS OCCASIONALLY. CONTACTS SHOULDNOT BE WORN  
WHILE WORKING WITH THIS MATERIAL. INGEST: DO NOT INDUCE VOMITING  
DRINK 1 OR 2 GLASSES OF WATER. CALL A DR. IN ALL THE ABOVE CASES.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:20F/-6C  
Lower Limits:1.0  
Upper Limits:10  
Extinguishing Media:DRY CHEMICAL, FOAM, CO2  
Fire Fighting Procedures:WEAR SC  
BA AND FULL PROT CLOTHING. WATER MAY BE  
USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND  
POSSIBLE AUTO IGNITION OR EXPLOSION.  
Unusual Fire/Explosion Hazard:KEEP CONT TIGHTLY CLOSED. VAPORS CAN  
TRAVEL ALONG THE GROUND TO IGNITION SOURCE.CONTAINERS MAY EXPLODE  
WHEN EXPOSED TO EXTREME HEAT & MAY CAUSE HEALTH HAZARDS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. MINIMIZE  
BREATHINGOF

VAPORS AND AVOID SKIN CONTACT. ABSORB WITH AN INERT MATERIAL. SHOVEL RECLAIMED LIQUID AND ABSORB-ENT INTO RECOVERY OR SALVAGE DRUM FOR DISPOSAL. DIKE TO PREVENT FURTHER MOVEMENT.

===== Handling and Storage =====

Handling and Storage Precautions: AVOID STORAGE IN HIGH TEMPERATURES OR AREAS NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME OR CUT ON EMPTY DRUMS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR AN APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR USE.

Ventilation: SUFFICIENT VENTILATION SHOULD BE PROVIDED TO KEEP THE AIR CONCENTRATION BELOW THE APPLICABLE OSHA AND T

Protective Gloves: CHEMICAL RESISTANT GLOVES

Eye Protection: CHEMICAL GOGGLES, SAFETY GLASSES

Other Protective Equipment: AS NEEDED TO PREVENT SKIN CONTACT

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING, OR USING RESTROOM.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 175-302F

Decomp Temp: Decomp Text: NE

Vapor Density: >AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: SL

IGHT

Appearance and Odor: LIQUID, ODOR OF SOLVENTS

Percent Volatiles by Volume: 54.51

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS

Stability Condition to Avoid: HIGH TEMPERATURES, SHOCK FROM DROPPING.

Hazardous Decomposition Products: CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE

Conditions to Avoid Polymerization: HIGH TEMPERATURES, SHOCK FROM DROPPING.

===== Di

Waste Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should

seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.