

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS BLACK 17038 -- 8010-00-527-2053
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS BLACK 17038

MSDS Date:03/23/1988

FSC:8010

NIIN:00-527-2053

MSDS Number: BHBGP

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-733-1361

Prepar

er's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:MINERAL SPIRITS (VP MM HG @

20 DEG C2)
CAS:64475-85-0
RTECS #:PY8240000
OSHA PEL:500PPM/MG/CUM 2950
ACGIH TLV:100PPM/MG/CUM 525

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:VOC. 4.0 LB/GL LESS WATER&NPRS* 480 G/L LESS WATER,VOC 10.4
LB/GAL SOLIDS 1248 G/L SOLIDS
RTECS #:9999999VO

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO
OSHA:NO

Health Hazards Acute and Chronic:CAN CAUSE GASTROINTESTINAL, EYE, SKIN
IRRITATION, NAUSEA AND VOMITING. ASPIRATION OF MATERIAL INTO LUNG
MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Effects of Overexposure:HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL
NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY
HEADACHES,DIZZINESS,NAUSEA AND CONFUSION. PROLONGED & REPEATED
OVEREXPOSURE TO SOLVENTS WITH BRAIN & NERVOUS SYST EM DAMAGE.

=====
===== First Aid Measures =
=====

First Aid:SWALLOWING-DO NOT INDUCE VOMITING.CALL POISON CONTROL CENTER.
INHALATION:REMOVE TO FRESH AIR IMMEDIATELY. IF BREATHING HAS
STOPPED,GIVE ARTIFICIAL RESPIRATION & GET MEDICAL HELP IMMEDIATELY.
EYE-FLUSH WITH LARGE AMOUNTS OF WATER AT LEAST 15 MINUTES.
SKIN-REMOVE CONTAMINATED CLOTHING.WASH WITH SOAP AND WATER. GET MED
HELP IF IRRITATION PERSISTS.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:SCC
Flas

h Point:102F/39C

Extinguishing Media:USE NFPA CLASS B FIRE EXTING CARBON DIOX ALL PURPOSE DRY CHEM OR ALCOHOL FOAM POLYMER FOAM IS PREFERRED FOR LG FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE,USE TO COOL EXPOSED CONTAINERS, IF WATER IS USED, FOG NOZZLES ARE PREFERRABLE.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.OBTAIN MEDICAL ATTENTION.SYMPTOMS NOT IMMEDIATELY APPARE
NT.MAY EXPLODE IF EXPOSED TO HIGH HEAT

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. DIKE AND CONTAIN SPILL WITH INERT MATERIAL. TRANSFER LIQUIDS TO COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL. USE ONLY NON-SPARKING TOOLS.PREVENT CONTAMINATION OF SEWERS,STREAMS, AND GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LG QTY IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. EMPTY CONTAINERS MUST NOT BE WASHED AND RE-USED. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT EMPTY CONTAINER. DRUM NOT PRESS VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED VENTILATION AREAS NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR MAY BE REQ IF SPRAYING A MECHANICAL PREFILTER MAY BE REQ. CONFINED AREAS USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.SEE OSHA 29CFR1910.134,AMER IND HYGIENE ASSOC

Ventilation:GENERAL DILUTION & LOCAL EXHAUST VENT.IN SUFFICIENT VOLUME TO KEEP CONCENTRATIONS INGREDIENTS IN SECT II BELOW LIMIT STD

Protective Gloves:SOLVENT IMPERMEABLE GLOVES ARE REQUIRED.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Supplemental Safety and Health

th

RCRA CLASSIFICATION; THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED A HAZARDOUS WASTE BASED ON ITS IGNITABILITY CHARACTERISTIC, I.E. HAS A FLASH POINT OF 140 DEG F, OR LESS. THE PROPER RCRA CLASSIFICATION WOULD BE D001.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:280F/388F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.
Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DI
SPOSE IAW FED, ST & LOCAL LAWS. INCINERATE ONLY
IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.
OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE
MATERIALS. CONTAMINATED ABSORBANT MAY BE DISPOSED IN A HAZARDOUS
WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.