

ATOCHEM INC. FOREX FIRE EXTINGUISHANTS -- HALON 1211;PYROFORANE 1211;FOREX 1211 --
6830-00-965-2309

=====
===== Product Identification =====

Product ID:HALON 1211;PYROFORANE 1211;FOREX 1211
MSDS Date:10/14/1987
FSC:6830
NIIN:00-965-2309
MSDS Number: BHBTS
=== Responsible Party ===
Company Name:ATOCHEM INC. FOREX FIRE EXTINGUISHANTS
Address:266 HARRISTOWN RD
Box:607
City:GLEN ROCK
State:NJ
ZIP:07452
Cou
ntry:US
Preparer's Name:SAFETY & ENVIRONS AFFAIRS
CAGE:MO388
=== Contractor Identification ===
Company Name:ATOCHEM INC FOREX FIRE EXTINGUISHANTS
Address:266 HARRISTOWN RD
Box:607
City:GLEN ROCK
State:NJ
ZIP:07452
Country:US
Phone:800-424-9300 (CHEMTREC)
CAGE:5P418
Company Name:ATOCHEM INC. FOREX FIRE EXTINGUISHANTS
Address:266 HARRISTOWN RD
Box:607
City:GLEN ROCK
State:NJ
ZIP:07452
Country:US
CAGE:MO388

=====
===== Composition/Information on Ingredients =====

Ingred Name:BROMOCHLO

RODIFLUOROMETHANE

CAS:353-59-3

RTECS #:PA5250500

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE-CONTACT WITH LIQUID CAN CAUSE
BURNS. SKIN-CONTACT WITH LIQUID CAN CAUSE FROSTBITE. INHALATION-NO
TROUBLE OBSERVED AT CONCENTRATIONS BELOW 20,000PPM. AT HIGHER
CONCENTRATIONS, NERVOUS TROUBLES AND POSSIBLE OF CARDIAC

IRREGULARITIES.

Explanation of Carcinogenicity:HALON 1211 IS NOT CLASSIFIED AS A
CARCINOGEN BY IARC, NTP OR OSHA.

Medical Cond Aggravated by Exposure:NOTE TO PHYSICIAN: PRODUCT IS AN
ASPHYXIANT AND MANY INDUCE CARDIAC MUSCLE SENSITIZATION TO
EPINEPHRINE-LIKE COMPOUNDS. DO NOT GIVE ADRENALIN OR SIMILAR
SYMPATHOMIMETIC DRUGS.

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH FLOWING WATER FOR 15 MIN. GET MED ATTN.
SKIN-FLUSH WITH WATER. CALL PHYSICIAN IF FROSTBITE SYMPTOMS OCCUR.
INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN. IF NOT BREATHING
GIVE ARTIFICIAL RESPIRATION. PREFERABLY MOUTH TO MOUTH.DO NOT
GIVE EPINEPHRINE. INGESTION-DO NOT INDUCE VOMITING IF PATIENT IS
UNCONSCIOUS OR HAVING CONVULSIONS.

===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE
Extinguishing Media:NON-FLAMMABLE PRODUCT-HALON 1211 IS USED AS A FIRE
EXTINGUISHING AGENT ITSELF.
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS MAY BE
NECESSARY IF CYLINDER RUPTURES OR RELEASES PRODUCT UNDER FIRE
CONDITIONS.
Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION GIVES TOXIC FUMES
(HYDROBROMIC, HYDROCHLORIC, HYDROFLURIC ACIDS, POSSIBLE FREE
HALOGENS AND CARBONYL HALIDES). CONT CAN RUPTURE UNDER FIRE

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA, ESPECIALLY LOW AREAS WHERE
HEAVY VAPORS MIGHT ACCUMULATE

HT COLLECT. REMOVE HOT METAL SURFACES OR SOURCE OF
NON-EXTINGUISHED FLAMES.

Neutralizing Agent:NONE LISTED.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AT TEMP BELOW 125F IN A WELL
VENTILATED AREA STORAGE & HANDLING PRECAUTIONS AS APPLICABLE TO
LIQUIFIED GASES UNDER PRESSURE.

Other Precautions:NONE LISTED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHI
NG APPARATUS IS REQUIRED

IF A LARGE SPILL OCCURS IN A CONFINED AREA.UNDER NORMAL CONDITIONS
NO RESPIRATORY PROTECTION IS REQUIRED WHEN USING THIS PRODUCT.

Ventilation:LOCAL EXHAUST RECOMMENDED. MECHANICAL REQ IN LOW AREAS
WHERE VAPORS MAY COLLECT.

Protective Gloves:YES WHEN HANDLING LIQUIFIED GAS.

Eye Protection:CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:NONE LISTED.

Supplemental Safety and Health
NONE LISTED.

=====
===== Physical/Chemical Properties =====

=====
=====

Boiling Pt:B.P. Text:25F

Vapor Pres:1758 MM HG

Vapor Density:5.97@68F

Spec Gravity:1.815 G/CC@68F

Evaporation Rate & Reference:LIQUIFIED GAS

Solubility in Water:NON-MISCIBLE

Appearance and Odor:COLORLESS, SLIGHT ETHERAL ODOR.

Percent Volatiles by Volume:100

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACTIVE METALS SUCH AS ALUMINUM AND MAGNESIUM, AND FIRES INVOLVING METAL
HYDRIDES.

Stability Condition to Avoid:EXPO

SURE TO FLAMES OR HOT SURFACES ABOVE
850F WILL CAUSE DECOMPOSITION.

Hazardous Decomposition Products:AT TEMP >850F TOXIC FUMES
(HYDROBROMIC, HYDROCHLORIC & HYDROFLUORIC ACIDS.POSSIBLY FREE
HALOGENS & CARBONYL HALIDES).

===== Disposal Considerations =====

Waste Disposal Methods:COMPLY WITH ALL FEDERAL,STATE AND LOCAL
REGULATIONS. RECLAIM IN SUITABLE VAPOR RECOVERY EQUIPMENT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.