

AIR PRODUCTS AND CHEMICALS, INC. -- OXYGEN, LOX (LIQUID ONLY) GOX (GAS ONLY) --
6830-00-169-0805

===== Product Identification =====

Product ID:OXYGEN, LOX (LIQUID ONLY) GOX (GAS ONLY)

MSDS Date:11/18/1987

FSC:6830

NIIN:00-169-0805

MSDS Number: BHDBG

=== Responsible Party ===

Company Name:AIR PRODUCTS AND CHEMICALS, INC.

Address:2043 S 35TH ST

Box:11393

City:ALLENTOWN

State:PA

ZIP:18195

Country:US

Info Phone Num:215-481-8257

Emergency Phone Num:1-800-523-9374 IN PA:1-800-322-9092

CAGE:00742

=== Contractor Identification ===

Company Name:AIR PRODUCTS AND CHEMICALS INC

Address:7201 HAMILTON BLVD

Box:City:ALLENTOWN

State:PA

ZIP:18195-1501

Country:US

Phone:800-345-3148/ 800-752-1597

CAGE:00742

Company Name:OXYGEN SALES AND SERVICE INC

Address:2043 S 35TH ST

Box:11393

City:TACOMA

State:WA

ZIP:98411-0393

Country:US

CAGE:5H199

===== Composition/Information on Ingredients =====

=

Ingred Name:OXYGEN, LOX (LIQUID ONLY), GOX (GAS ONLY)

CAS:7782-44-7

RTECS #:RS2060000

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:BREATHING PURE OXYGEN AT ONE ATMOS,MAY PRODUCE COUGH & CHEST PAINS W/IN 8-24 HOURS.CONCENTRATIONS OF 60% MAY PRODUCE THESE SYMPTOMS IN SEVERAL DAYS.AT TWO ATMOS SYMPTOMS OCCUR IN 2-3 HRS

.PARTIAL PRESSURE OF OXY IN EXCESS OF TWO ATMOS

MAY PRODUCE A VARIETY OF CENTRAL NERVOUS SYS MANIFESTATIONS.

Effects of Overexposure:LIQUID OXYGEN OR COLD GAS WILL FREEZE TISSUES & CAN CAUSE SEVERE CRYOGENIC (EXTREMELY LOW TEMPERATURE)BURNS.

=====
===== First Aid Measures =====

First Aid:IF CRYOGENIC LIQUID OR COLD BOIL-OFF GAS CONTACTS A WORKER'S SKIN OR EYES,FROZEN TISSUES SHOULD BE FLOODED OR SOAKED W/TEPID WATER(105-115F;41-46C).DO NOT USE

HOT WATER.BURNS WHICH RESULT IN

BLISTERING OR DEEPER TISSUE FREEZING SHOULD BE SEEN PROMPTLY BY A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:NA

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:NA

Fire Fighting Procedures:OXYGEN IS NONFLAMMABLE,BUT SUPPORTS & VIGOROUSLY ACCELERATES COMBUSTION OF FLAMMABLES.TO FIGHT FIRES,SHUT OFF SOURCES OF OXYGEN & FIGHT LIKE CONVENTIONAL FIRE.

Unusual Fire/Explosion Hazard:OXYGEN IS NONFLAMMABLE,BUT SUPPORTS &

VIGOROUSLY ACCELERATES COMBUSTION OF FLAMMABLES.SOME MATERIALS WHICH ARE NONCOMBUSTIBLE IN AIR WILL BURN IN PRESENCE OF OXY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:PREVENT LIQ OXY FROM CONTACTING

GREASE,OIL,ASPHALT OR COMBUSTIBLES.VENTILATE AREA TO EVAP & DISPERSE OXY.FLUSH AREA W/LARGE QTY'S OF WATER.DO NOT ENTER AREAS OF HIGH OXYGEN CONCENTRATION,WHICH CAN SATURATE CLOTHING & INCREASE ITS FLAMMABILITY.

=====
Handling and Storage
=====

Handling and Storage Precautions:USE/STORE IN WELL VENT AREA.DO NOT DRAG,ROLL OR SLIDE.USE SUITABLE HAND TRUCK.KEEP CYLS AWAY FROM SOURCES OF HEAT.SEGREGATE FULL/EMPTY CYLS.

Other Precautions:OXYGEN IS NOT TO BE USED AS A SUBSTITUTE FOR COMPRESSED AIR.APPLICATIONS SUCH ASCLEANING,DUSTIN,POWERING PNEUMATIC TOOLS,ETC.,ARE NOT SAFE DUE TO LUBRICATING OILS & OTHER MATERIALS PRESENT.USE ONLY W/ EQUIP SPEC DESIG NED & CLEANED FOR OXY SV

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NA
Ventilation:YES
Protective Gloves:LOOSE-FITTING GLOVES SUCH AS LEATHER
Eye Protection:CHEMICAL GOGGLES/SAFETY GLASSES
Other Protective Equipment:NA
Supplemental Safety and Health NK

=====
Physical/Chemical Properties
=====

HCC:G4
Boiling Pt:B.P. Text:-297.3F *
Vapor Pres:NA
Vapor Density:@68F 20C*
Spec Gravity:@BOILING POINT*
Solubility in Water:@77F 25C *
Appearance and Odor:GASEOUS OXYGEN IS COLORLESS & ODORLESS.LIQUID OXYGEN IS PALE BLUE & ODORLESS

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
ALL FLAMMABLES,ESPECIALLY PETROLEUM PRODUCTS,ASPHALT,OTHER VOLATILE FLAMMABLES.
Stability Condition to Avoid:MATERIALS WHICH BURN IN AIR WILL BURN VIOLENTLY IN ATMOS RICHER THAN APPROX 25% OXYGEN.
Hazardous Decomposition Products:NONE

=====
Dispo
=====

sal Considerations =====

Waste Disposal Methods:ALLOW LIQ OXY TO EVAP IN A WELL VENT OUTDOOR AREA.VENT OXY GAS TO OUTSIDE LOCATION.DISPOSAL SITE SHOULD BE REMOTE FROM WORK AREAS,OPEN FLAMES OR SOURCES OF IGNITION & COMBUSTIBLES.FLUSHING W/WTR WILL INCREASE THE VAPORIZATION RATE OF THE LIQUID.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.