

RANBAR TECHNOLOGY INC. D/B/A -- VARNISH, MOISTURE AND FUNGUS RESISTANCE --
8010-00-180-6343

=====
===== Product Identification =====

Product ID:VARNISH, MOISTURE AND FUNGUS RESISTANCE

MSDS Date:06/14/1989

FSC:8010

NIIN:00-180-6343

MSDS Number: BHDBL

==== Responsible Party ===

Company Name:RANBAR TECHNOLOGY INC. D/B/A

Address:1114 WM. FLINN HIGHWAY

City:GLENSHAW

ZIP:15116

Country:US

Info Phone Num:412-48

6-1111

Emergency Phone Num:412-486-1111

Preparer's Name:PAUL R. YINGST

CAGE:DO583

==== Contractor Identification ===

Company Name:BALL CHEMICAL CO

Address:1114 WILLIAM FLINN HIGHWAY

Box:City:GLENSHAW

State:PA

ZIP:15116-2316

Country:US

Phone:412-486-1111

CAGE:51747

Company Name:RANBAR TECHNOLOGY

Address:1114 WM. FLINN HIGHWAY

Box:City:GLENSHAW

Phone:412-486-1111

CAGE:DO583

=====
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:64742-88-7

Fraction by

Wt: 28%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM

Ingred Name:TUNG OIL
CAS:67746-14-9
Fraction by Wt: 42%
Other REC Limits:NONE SPECIFIED

Ingred Name:SALICYLANILIDE
CAS:87-17-2
RTECS #:VN7850000
Fraction by Wt: 3-4%
Other REC Limits:NONE SPECIFIED

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 25%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Report

s of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:VAPORS MAY IRRITATE THE EYES AND
RESPIRATORY TRACT; IN HIGH CONCENTRATION, DEPRESSION OF
CENTRAL NERVOUS SYSTEM. PROLONGED OR REPEATED CONTACT WITH SKIN
MAY RESULT IN SKIN IRRITATION AND DERMATITIS.

Effects of Overexposure:EYE IRRITATION, IRRITATION OF MUCOUS MEMBRANES,
HEADACHE, DIZZINESS, NAUSEA, OR LOSS OF CONSCIOUSNESS.

Medical Cond Aggravated by Exposure:DRY SKIN, DERMATITIS, CHEMICAL
P

ENUNONITTA, PULMONARY EDEMA/HEMORRHAGE, AND DEPRESSION OF
CENTRAL NERVOUS SYSTEM.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH WATER. SKIN CONTACT: REMOVE
CONTAMINATED CLOTHING AND WASH WITH SOAP AND WATER. INGESTION: DO
NOT INDUCE VOMITING. GET MEDICAL HELP.

=====
===== Fire Fighting Measures =====

Flash Point:110F 43C
Lower Limits:1.0
Upper Limits:11.0
Extinguishing Media:USE FOAM

, WATER FOG, CARBON DIOXIDE OR DRY CHEMICAL

Fire Fighting Procedures:FIGHT FIRE IN CONFINED SPACE BY WEARING NIOSH APPROVED S.C.B.A., BUNKER COATS, RUBBER GLOVES, & HELMET W/FACE SHIELD. COOL FIRE EXPOSED DRUMS WITH WATER.

Unusual Fire/Explosion Hazard: STORAGE CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRE SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILD-UP WHICH COULD RESULT IN RUPTURING THE CONTAINER

===== Accidental Release Measures =====

S

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. STOP SPILL AT SOURCE. DIKE AND CONTAIN SPILL. SOAK UP SPILL WITH A SUITABLE ABSORBENT. REPORT ALL SPILLS GREATER THAN 5 GALLONS. CLEAN.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL PLACE. REMOVE WASTE FROM WORKPLACE WITHIN 3 MONTHS.

===== Exposure Controls/Personal Protection =====

==

Respiratory Protection: IN POORLY VENTILATED AREAS, WEAR A NIOSH/MSA CHEMICAL CARTRIDGE RESPIRATOR.

Ventilation: LOCAL EXHAUST: OPEN WINDOWS, DOORS.

MECHANICAL: EXHAUST FAN

Protective Gloves: SOLVENT RESISTANT MATERIAL

Eye Protection: SAFETY GLASSES, FACE SHIELD

Other Protective Equipment: SAFETY SHOES

Work Hygienic Practices: WASH HANDS BEFORE EATING AND GOING TO THE REST ROOM; DO NOT SMOKE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

=====

Boiling Pt: B.P. Text: 315 - 390F

Vapor Pres: < 10

Vapor Density: 4.6

Spec Gravity: .9

Evaporation Rate & Reference: < 1 (BUTYL ACETATE = 1)

Solubility in Water: SLIGHT

Appearance and Odor: DARK AMBER LIQUID, MILD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: KEEP PRODUCT AWAY FROM INTENSE HEAT SOURCES AND OPEN FLAMES.

=====

===== Disposal Considerations =====

Waste Disposal Methods: PLACE THE "USED" ABSORBENT IN A NON-LEAKING CONTAINER, SEAL TIGHTLY, & MARK FOR WASTE DISPOSAL THE HAZARDOUS WASTE NO. IS D001

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.