

CSD, INC. -- THINNER, AIRCRAFT COATING -- 8010-00-181-8079

=====
Product Identification
=====

Product ID:THINNER, AIRCRAFT COATING

MSDS Date:09/17/1986

FSC:8010

NIIN:00-181-8079

MSDS Number: BHDBT

=== Responsible Party ===

Company Name:CSD, INC.

Address:#5 HACKBERRY

City:CUT & SHOOT

State:TX

ZIP:77302

Country:US

CAGE:KO005

=== Contractor Identification ===

Company Name:CSD INC. (PRE 1985 NAME: MATTHEWS, INC)

Address:420 SEABOARD DRIVE

Box:City:MATTHEWS

State:NC

ZIP:28105-5073

Country:US

Phone:704-821-9822

CAGE:5W216

Company Name:CSD, INC.

Address:5 HACKBURY ST

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:KO005

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 8% MAX

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 12% MAX

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 40-45%

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 10-13%

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/20

0STEL;9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 30-33%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:LIVER AND KIDNEY DAMAGE. BRAIN CELL

DAMAGE MAY RESULT FROM LONG TE

RM INHALATION OF TOLUENE VAPORS.

Effects of Overexposure:EYE:MAY BE IRRITANT; SKIN: PROLONGED/REPEATED
MAY RESULT IN DERMATITIS. INHAL: RESPIRATORY TRACT
IRRITATION, ANESTHESIA IN HIGH CONCENTRATIONS, NAUSEA AND
VOMITING.

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES &
SEEK IMMEDIATE MEDICAL ATTENTION. SKIN: WASH WITH LARGE QUANTITIES
OF WATER & SEEK MEDICAL ATTENTION. INHAL:DIZZI
NESS,LIGHTHEADEDNESS
OCCUR VI CTIM SHOULD SEEK FRESH AIR. IF VICTIMIS NOT BREATHING GIVE
ARTIFICIAL RESPIRATION & SEEK MEDICAL ATTENTION
IMMEDIATLYINGST:CONTACT PHYSICIAN IMMEDIATELY OR POISON CENTER
213-664-2121 (24HOUR NO.)

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:42F/5.56C
Lower Limits:1.7
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:USE S.C.B.A. FOR FIRE FIGHTERS. WATER MAY BE
UNSUITA
BLE AS AN EXTINGUISHING MEDIA, BUT HELPFUL IN KEEPING
ADJACENT CONTAINERS COOL.
Unusual Fire/Explosion Hazard:AVOID SPREADING BURNING LIQUID WITH WATER
USED FOR COOLING PURPOSES. KEEP WORK AREAS FREE OF HOT METAL
SURFACES AND OTHER SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SOURCES OF IGNITION/HT MTL SURFACES
ISOLATED FROM SPILL.FLUSH SPILLED MATL WITH LARGE QUANTITY OF
WATER. SMALL SPILLS CAN
BE ABSORBED INTO APPR. ABSORBANT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS COOL, DRY, ADEQUATE
VENTILATION, & AWAY FROM SOURCES OF IGNITION. KEEP PRODUCT
CONTRNCLOSED WHEN NOT IN USE.
Other Precautions:AVOID INHALATION OF VAPORS. SHOULD CONTACT BE MADE,
REMOVE SATURATED CLOTHING AND FLUSH AFFECTED AREAS WITH WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:D

DEPENDS ON VAPOR CONCENTRATION ABOVE THE TLV.;

USE A NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK.

Ventilation:LOCAL EXHAUST OR MECHANICAL IF SUFFICIENT TO KEEP VAPOR CONCENTRATION WITHING SPECIFIED TLV RANGES.

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:SAFETY GLASSES,CHEM GOGGLES/FACESHIELDS

Other Protective Equipment:IMPERMEABLE APRONS, EYE WASHES AND SAFETY SHOWERS

Supplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====
=====

Boiling Pt:B.P. Text:175F/79C

Melt/Freeze Pt:M.P/F.P Text:-20F

Vapor Pres:35.1

Vapor Density:3.4

Spec Gravity:.887

Evaporation Rate & Reference:ETHER 16.8

Solubility in Water:5%

Appearance and Odor:CLEAR, LITTLE IF ANY COLOR, CHARACTERISTIC ODOR.

Percent Volatiles by Volume:100

=====
===== Stability and Reactivity Data =====
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS,ACIDS OR BASES, SELECTED AMINES,
HALOGENS/HALOGENS COMPOUNDS, ALKALI

ES

Hazardous Decomposition Products:THERMAL DECOMPOSITION IN THE PRESENCE
OF AIR MAY YIELD CARBON MONOXIDE/DIOXIDE.

=====
===== Disposal Considerations =====
=====

Waste Disposal Methods:DISPOS OF IN ACCORDANCE W/FEDERAL,STATE,LOCAL, &
COUNTY REGULATIONS. PREVENT LIQUID FROM ENTERING SEWERS,STORM
DRAINS,SEWAGE TREATMENT/DRAINAGE SYS.AND NATURAL WATERWAYS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated

for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.