

CSD, INC. -- MINERAL SPIRITS,TT-T-291F, TYPE 1 -- 8010-00-246-6116

=====
===== Product Identification =====

Product ID:MINERAL SPIRITS,TT-T-291F, TYPE 1

MSDS Date:10/01/1986

FSC:8010

NIIN:00-246-6116

MSDS Number: BHDCZ

=== Responsible Party ===

Company Name:CSD, INC.

Address:#5 HACKBERRY

City:CUT & SHOOT

State:TX

ZIP:77302

Country:US

CAGE:KO005

=== Contractor Identification ===

Company Name:CSD INC. (P
RE 1985 NAME: MATHEWS, INC)

Address:420 SEABOARD DRIVE

Box:City:MATTHEWS

State:NC

ZIP:28105-5073

Country:US

Phone:704-821-9822

CAGE:5W216

Company Name:CSD, INC.

Address:5 HACKBURY ST

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:KO005

=====
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS REGULAR

CAS:64741-41-9

Fraction by Wt: 35%

ACGIH TLV:500 PPM

Ingred Name:66/3 MINERAL SPIRITS

CAS:64742-88-7

Fraction by Wt: 65%

ACGIH TL

V:100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:VAPORS MIGHT AFFECT CONTROL OF NERVOUS SYSTEM
AND CAUSE RESPIRATORY IRRITATION. ADVANCED TEMPERATURES WOULD
INCREASE THIS HAZARD. ANESTHESIA IN HIGH CONCENTRATNEYE: IRRITANT

=====
First Aid Measures
=====

First Aid:EYE: WASH GENTLY W/PLENTY WTR FOR 15 MINS. GET MEDICAL
ATTENTION.
SKIN: REMOVE CONTAMINATED CLOTH & WASH
W/SOAP & WATER. SEEK MEDICAL ATTENTION. INHAL: SEEK AIR FREE OF
VAPORS. IF BREAT HING STOPS GIVE ARTIFICIAL RESPIRATION& SEEK
MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING, UNLESS
DIRECTED BY PHYSICIAN. GET IMMEDIATE MEDICAL ATTENTION AND/OR
ADVICE.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:105F/40.56C
Lower Limits:6.0
Upper Limits:0.9
Extinguishing Media:MECHANICAL
FOAM, DRY CHEMICAL, WATER FOG, CO2
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS. STRAIGHT
WATER STREAM WOULD SPREAD OIL FIRE.
Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL
SURFACES AND OTHER SOURCES.

=====
Accidental Release Measures
=====

Spill Release Procedures:AVOID ALL SOURCES OF IGNITION.
STAY UPWIND, COLLECT & DISPOSE OF SPILLS. STOP DISCHARGE IF
POSSIBLE. COVER W/INERT MATERIAL. USE NONSPARKING TO
OLS FOR CLEANUP.
KEEP OUT OF SEWERS, WATERWAYS, AND DRAINS.

=====
Handling and Storage
=====

Handling and Storage Precautions:COMPLY WITH LOCAL FIR REGULATIONS.
HANDLE AS CLII,COMBUSTIBLE LIQUID.
Other Precautions:CONTACTS FIRE AUTHORITIES,NOTIFY HEALTH/POLLUTION
CONTROL AGENCIES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS, WITH
ADEQUATE VENTILATION.
Ventilati

on:VENTILATE TO FIRE SAFE AREA.

Protective Gloves:RECOMMENDED

Eye Protection:GOGGLES

Other Protective Equipment:IMPERMEABLE APRON, EYE WASHES, & SHOWERS
AVAILABLE IN WORK AREAS.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:310-405F

Vapor Pres:1.8 @ 60F

Vapor Density:5.05

Spec Gravity:.7741

Evaporation Rate & Reference:0.08

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WATER WHITE LIQUID, MILD APLIPHATI
C HYDROCARBON

ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, OR BASES & SELECTED AMINES.

Stability Condition to Avoid:NA

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.