

DENNISON STATIONERY PRODUCTS COMPANY -- CARTER'S RUBBER CEMENT --
8040-00-262-9040

=====
Product Identification
=====

Product ID:CARTER'S RUBBER CEMENT
MSDS Date:07/19/1988
FSC:8040
NIIN:00-262-9040
MSDS Number: BHDFB
=== Responsible Party ===
Company Name:DENNISON STATIONERY PRODUCTS COMPANY
Address:300 HOWARD STREET
City:FRAMINGHAM
State:MA
ZIP:01701
Country:US
Emergency Phone Num:508-879-0511
X4636
CAGE:HO918

=== Contractor Identification ===
Company Name:DENNISON STATIONARY PRODUCTS CO
Address:300 HOWARD STREET
Box:City:FARMINGTON
State:MA
ZIP:01701
Country:US
Phone:508-879-0511
CAGE:HO918

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPTHA
CAS:67472-89-8
Fraction by Wt: 88.6%
Other REC Limits:400 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of

Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:OVEREXPOSURE CAN LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION PRODUCING HEADACHES, DIZZINESS, NAUSEA, AND LOSS OF CONSCIOUSNESS.

Effects of Overexposure:HEADACHES, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS.

Medical Cond Aggravated by Exposure:SKIN DISEASE, CHRONIC RESPIRATORY DISEASE

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER, CALL PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. CALL PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. LAUNDRY CLOTHING. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:< 10F/-24C

Lower Limits:7.0

Upper Limits:1.1

Extinguishing Media:CO2, FOAM, DRY CHEMICAL, WATER FOG OR SPRAY

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING INCLUDING NIOSH

SELF-CONTAINED BREATHING APPARATUS COOL EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:IN CASE OF LARGE FIRES, ALSO COOL SURROUNDING EQUIPMENT AND STRUCTURES WITH WATER. DO NOT MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID OPEN FLAMES OR SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. ADD ABSORBENT (SAWDUST, SAND ETC.) TO SPILL AREA. TO AVOID SPILLING, DEEP CAP TIGHTLY CLOSED WHEN NOT USING.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES, SPARK SOURCES, SPLASH SPILLING, EXCESSIVE HEAT. KEEP CONTAINERS CLOSED WHEN NOT USING.

Other Precautions:CAREFULLY READ ALL DIRECTIONS AND CAUTIONS ON PRODUCT CONTAINER.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST IF NEEDED TO CONTROL VAPOR. MECHANICAL (GENERAL)

VENTILATION EXPLOSION PROOF EQUIPMENT.

Protective Gloves:PVA OR NITRILE RUBBER

Eye Protection:SAFETY GLASSES/GOGGLES

Work Hygienic Practices:WASH HANDS BEFORE EATING, DO NOT SMOKE OR USE NEAR OPEN FLAME.

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:151 - 225F

Vapor Pres:250 @ 100F

Vapor Density:3.3

Spec Gravity:.72

Evaporation Rate & Reference:5.8 (BUTYL ACETATE = 1)

Solubility in Water:NEGLIGIBLE

Appearance

Color and Odor:BUFF COLOR LIQUID WITH HYDROCARBON ODOR.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS LIKE CHLORINE

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

=====
Disposal Considerations
=====

Waste Disposal Methods:EVAPORATE AND PEEL RESIDUE FROM SURFACE. TREAT AS HYDROCARBON.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of thi

s information to their
particular situation.